



EDITION N° 19

AFTERMARKET PRODUCTS CATALOGUE

SCHRADER PACIFIC®
Tire Hardware Solutions



LIGHT VEHICLE

This catalogue presents the Schrader Pacific tire hardware solution products sold when it was released. It is a working tool for professionals who will find in it the most commonly used valves, accessories, tools and equipment for garages.


We provide some technical information to help you use the products under optimal conditions and thus facilitate your maintenance operations. Our technical and sales teams are at your service to provide you the support you need.

Terms and Conditions of Sale

By submitting an order, you accept the terms and conditions of sale regarding our prices and invoices. The terms and conditions may not under any circumstances be cancelled by contrary terms and conditions of sale.

Updates

Schrader S.A.S. reserves the right to make any modifications deemed appropriate to this catalogue or the products themselves without prior notification. You will find in our price list the exact list of products sold. Our customer service department is here to help you with any specific procurement or training issues.



CHAPTERS

Presentation

1 [Passenger vehicle valves](#)

2 [Valve cores and caps](#)
[Air conditioning products](#)

3 [Balancing products](#)

4 [Inflation/compressed air equipment](#)

5 [Tire and inner tube repair products and parts](#)

6 [Repair tools and vulcanization equipment](#)

7 [Tire mounting products](#)
[WORKSHOP SERVICE RANGE and PPE](#)

8 [ETRTO index](#)
[Reference index: alphabetical and numerical](#)

HOW TO PLACE YOUR ORDER

Request your login and password to access your **shop.schrader-pacific.fr** account for the "Tire equipment and consumables" category.



www.shop.schrader-pacific.fr

To avoid any confusion when placing your order, we recommend that you include, FOR EACH PRODUCT:

- **the complete Schrader Pacific tire Hardware Solutions reference**, e.g.:
- **the Description**, e.g.: "MASTAIR tire inflator gauge in bar"
- **the quantity ordered**.

39000-00

The packaging indicated on our prices may not be broken into fractions. We thus reserve the right to round the quantity requested up to the quantity that is the next highest standard multiple.

CUSTOMERS France

Call Center:

Tel. 03 81 38 56 60

Fax +33 (0)3 81 38 56 81

Tire specialists and automobile distributors.

In France, and on customer request, any order for products in stock received before 3 p.m. can be delivered within 24 hours.

EXPORT CUSTOMERS

Call Center:

Tel. +33 (0) 381 38 56 27

Fax +33 (0)3 81 38 56 81

Network of distributors in Europe, Africa, the Middle East, the Far East and Asia.



TECHNICAL INFORMATION ABOUT THE PRODUCT

	Technical information about the product
	Product standards
	Diameter of the rim hole
	Website for more information
	Video available / Update via Internet
	Intra-Schrader Pacific tire Hardware Solutions or on-site training
	Part storage: Store parts, products and liquids away from light, in a dry, clean place and adhere to storage temperatures
	High-Quality product
	Premium Range and Better quality-price ratio
	Spare parts
	Schrader Pacific Tire Hardware Solutions After Sale Service
	Destruction in accordance with Directive 2022/96/EC
	Expiration date
	Identification of the different types of weights
	Safety sheet available
	Instructions on demand or on shop.schrader-pacific.fr
	Appropriate Personal Protection Equipment
	Trick product
	Light product
	Product favourites

TRAINING IN PONTARLIER & ON SITE



Training in Pontarlier & on site: Personalised service, customised offer

- Training centre recommended for professional training. Declaration registered under No. 43 25 01928 25 with the local government of the Franche-Comté Region.
- TPMS pressure sensors (repair, mounting, programming)
- Cold and hot tire repair
- Mounting and dismounting of tires.



AFTER SALE SERVICE

After sale service: A trained & experienced aftersales team



Mounting, calibration, repair and maintenance:

- Pressure gauges
- Hydropneumatic jacks
- tire re-groover
- Civil engineering and agricultural mounting tools
- Torque wrenches

For non-manufactured products, Schrader Pacific tire Hardware Solutions has obtained tool supplier approvals for internal aftersales services.


Service SAV Schrader SAS

Quai n° 2 - Rue Jean Mermoz

25300 Pontarlier - France

France => Tel.: +33 (0) 381 38 56 60

International => Tel.: +33 (0) 381 38 56 27



Chapter 1

Snap-in type rubber tubeless valve ORIGINAL
Schrader Pacific tire Hardware
Solutions, 50 years of experience= Quality & safety.

QUALITY AND SAFETY.

With its experience in new vehicle fitting with automobile manufacturers and tire manufacturers, Schrader Pacific tire Hardware Solutions offers in the aftermarket a complete range of tubeless valves compliant with ETRO and ISO standards.

VALVE REPLACEMENT AND MAINTENANCE.

WHY?

Valves are subject to a lot of strain:

- Bending from centrifugal force
- Extreme temperature change due to their close proximity to brake drums or discs
- Poor weather conditions and salty air, road salt, etc.
- Natural ageing of the rubber
- Corrosion of aluminium valves
- Hydrocarbons

MANUFACTURING AND LABORATORY TESTS.

APPROVED AND PROVEN QUALITY SYSTEM.

Rubber valves:

- Automatic 100% airtightness controls in production
- Ozone, bending and impact-proof
- Airtightness at temperatures from -40 to +100°C
- Blowout, placement and tear-off tests
- Over-pressure tests carried out at 13 bar for 2 mins.

Metal valves:

- Resistance to mechanical stresses
- Resistance to saline mist



PARTS DRAWINGS:

The valves, valve cores and caps are shown in the catalogue **to scale**.

CAR VALVES



TRADITIONAL CAR VALVES

- Rubber tubeless valves (snap-in)..... 12
TR412 - TR413 - TR414 - 414L - TR418.
- High-pressure rubber tubeless valves (snap-in).....13
TR600HP - TR801HP.
HP tubeless with nickel-coated brass base.
- Rubber tubeless valves for inner tube 14
TR13 - TR15 and ring.
- Metal tubeless valves in raw brass or in nickel-coated brass (clamp-in)..... 15
1533 - TR430 - TR416S - Especially for campers.
- Metal tubeless valves in nickel-coated brass (clamp-in) 16
TR416S.
- Light alloy tubeless valves (clamp-in)..... 16 - 17
- Rigid plastic extensions..... 17

RUBBER TUBELESS VALVES

11,5

COLD MAX 4,5 bar

MAX SPEED 210 km/h



Valves mounting tools ref. S4032-1 or 65027-67:

- Check that rim holes are free from burrs and have a smooth, flat rust-free surface.
 - NB: rubber valves must be mounted on all rim types (aluminium or steel) having a minimum thickness of 1,8 min. at maxi 3,5 mm.
- Very strong tools. • Over-pressure tests carried out at 13 bar.
 - Cold and heat resistance -40° to +100°C.




TR 412 (V2.03.6)		Quantity per box	Packs of 100 per box
(L)	S-4040-2	10	
(L)	S-4040-3	100	
(L)	S-4040-55		10
(L)	S-4040-66		5
(A)	66501-80		10

TR 413 (V2.03.1)		Quantity per box	Packs of 100 per box
(C)	R-1496-2	10	
(C)	R-1496-3	100	
(L)	S-4636-55		10
(L)	S-4636-66		5
(A)	66504-80		10

TR 414 (V2.03.2)		Quantity per box	Packs of 100 per box
(C)	R-0756-2	10	
(C)	R-0756-3	100	
(L)	S-4638-55		10
(L)	S-4638-66		5
(A)	66507-80		10

(C) OE valves assembled complete with core and plastic cap.
 (L) Standard AM valves assembled with core and sealing cap.
 (A) Standard AM valves delivered paired (core and cap not mounted).



414 L (V2.03.8)		Quantity per box	Packs of 100 per box
(C)	R-1878-2	10	
(C)	R-1878-3	100	
(L)	S-4640-55		10
(L)	S-4640-66		5
(A)	35167-69		10

TR 418 (V2.03.4)		Quantity per box	Packs of 100 per box
(C)	R-1799-2	10	
(C)	R-1799-3	100	
(L)	S-4642-55		10
(L)	S-4642-66		5
(A)	66513-80		10

TR 413 Chrome-plated		Quantity per box	Packs of 100 per box
	66505-68	10	
	66505-69	100	
	66505-80		10

TR 414 Chrome-plated		Quantity per box	Packs of 100 per box
	66508-69	100	
	66508-80		10


HIGH-PRESSURE RUBBER TUBELESS VALVES

Standard AM valves assembled with core and cap.

Valves OE approved



TR 600 HP [V3.23.1]	Quantity per box
43025-68	10
43025-69	100




TR 801HP	Quantity per box
65664-68	10


Standard AM valves assembled with core and cap.
• OE approved nickel-coated brass valves.



	Quantity per box
65752-68	10
65752-69	100



	Quantity per box
65753-68	10
65753-69	100




	Quantity per box
65754-68	10
65754-69	100

BRASS TUBELESS VALVES



(C) OE valves assembled complete with core and plastic cap.
(L) Standard AM valves assembled with core and sealing cap.

11,5



TYPE	Quantity per box
Scooter 41558-68	10

16



	TR 415 (V2.03.3)	Quantity per box	Packs of 100
(L)	S-4156-2	10	
(L)	S-4156-3	100	
(L)	S-4156-55		10

▶ VALVES FOR INNER TUBES

Valves for cold cure with butyl rubber spud sold unbuffed.



11,5

16

		Quantity per box
S-4008-1	TR 13 (V2.01.1)	1
S-4010-1	TR 15 (V2.01.2)	1

		Quantity per box
R-0990-2	Intermediate ring for valve mounting TR 13 in a 16 mm rim hole	10
R-0990-3		100


TUBELESS VALVES OR VALVES FOR INNER TUBES AND EXTENSION



- High speeds (top-of-the-line vehicles): at high speeds, valves are subjected to stress due to the centrifugal force.
 - Metal clamp-in tubeless valves are recommended for intensive use
 - Replace the sealing washer each time you remove the tire

8,5


Nut tightening torque: 3 to 5 N.m.



TR 430 (V1.11.1) For motorcycles	Quantity per box	Spare washer
S-4043-2	10	2 Seals 35127-68

9,7


Nut tightening torque: 12 to 15 N.m.



Nickel-coated	Quantity per box	Spare washer
R-1533-2	10	R-1419-2

11,5

Nut tightening torque: 3.5 to 4.6 N.m.




TR 416-S	Quantity per box	Spare washer
R-2103-2	10	R-2105-2

METAL TUBELESS VALVES

► LIGHT ALLOY (FOR LIGHT ALLOY WHEELS)


8,5

Nut tightening torque: 7 to 10 N.m.



(V1.10.1) For motorcycles	Quantity per box	Spare washer
R-1674-2	10	R-1709-2

8,5



For motorcycles	Quantity per box
42396-67	1

METAL TUBELESS VALVES




► NICKEL-COATED BRASS

11,5



Also suitable for Michelin alu truck wheels.

Nut tightening torque: 3 to 6 N.m.



TR 416-S (V2.05.1)	Quantity per box	Spare washer
S-4042-2	10	35440-68

TR 416-S (V2.05.1)	Quantity per box
S-4042-G	10


TR 416-S	Quantity per box	Spare washer
42039-68	10	35440-68
42039-69	100	

METAL TUBELESS VALVES


► LIGHT ALLOY (FOR LIGHT ALLOY RIMS)

Nut tightening: 10 to 12 N.m.


11,5 **MAXI 210** km/h



11,5



9,7



For motorcycles angled	Quantity per box
65252-68	10



(V2.04.1)	Quantity per box	Spare washer
R-1446-2	10	R-1524-2

	Quantity per box	Spare washer
R-1578-2	10	R-1419-2

PLASTIC RIGID EXTENSIONS TOTAL SEALING

▶ SHORT SKIRT

Tightening torque
Mounting on the valve nose:
0,4 to 0,7 N.m.






	Total length A (mm)	Useful length B (mm)	Quantity per bag
42563-68	61	53,5	10
43249-68	101	93,5	10
42564-68	140	132,5	10

▶ FOR LIGHT COMMERCIAL AND CAMPERS

11,5

PRESSIONS
>4,5 bar
POSSIBLES

Nut tightening torque: 12 to 15 N.m.



(V2.04.1)	Quantity per box	Spare washer
R-1510-2	10	R-1524-2

	Quantity per box	Spare washer
R-1914-2	10	R-1524-2

Nickel-coated	Quantity per box
65765-68	10

Good pressure is the first step in ensuring driver safety and the lifespan of a tire.

VALVE CORES AND CAPS COMPLIANT WITH ETRTO, ISO, ETC. STANDARDS

The valve cores and caps sold in resale are always original equipment manufacturers products, used in original fit and approved by auto manufacturers and tire manufacturers.

Airtightness is maintained by the combined action of the valve core and the sealing cap.

VALVE CORES:

- The valve core is what keeps the air in the tire or in the air conditioning system.
- It should be replaced with each mounting and dismounting operation.
- For inflation, use a connection that is in very good condition, with clean air.
- Adhere to the recommended torques.
- For installation of the valve stem with the correct torque, use tool 66690-67.

The valve cores presented in this catalogue are reserved for use with "automobiles".

CAPS:

The sealing cap is the only cap ensuring the airtightness of the valve. By preventing the introduction of a foreign body in the functional part of the valve stem and preventing any leak from the valve, the cap thus ensures the protection of the valve assembly and interior (tube, valve stem).

VALVE CORES AND CAPS



VALVE CORES AND CAPS

• Valve cores.....	20
• Valve caps	20
• Valve cores for air conditioning R134A and 1234yf	21
• Caps for air conditioning R134A and 1234yf	21
• Boxes for air conditioning R134A and 1234yf.....	22

VALVE CORES AND CAPS



STANDARD FLOW

Cores

Metallic caps



	(1) 37992-69 (2) 37992-80
Body material	Nickel-plated brass
Seal	Teflon
Tightness torque (N. m)	0,23 to 0,56
Operating pressure (bar)	0 to 14
Use	Core specially recommended for pressure sensors
Quantity per box	(1) 100 (2) 1000



	60166-71	R-0638-3	33792-69
Body material	Chrome-plated for valves 33651-68 and 33653-68	Sealing cap with core remover Nickel-plated brass	Knurled sealing cap Nickel-plated brass
Tightness torque (N. m)	0,2 to 0,35	0,2 to 0,35	0,2 to 0,35
ETRTO		V9.04.4	V9.04.3
Quantity per box	50	100	100

Caps



	(1) S-4000-3 (2) S-4000-5	(1) 30307-63 (2) 30307-53	30307-54	30307-57	30307-58
Body material	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene
Color	black	green	blue	yellow	red
Tightness torque (N. m)	0,2 to 0,3	0,2 to 0,3	0,2 to 0,3	0,2 to 0,3	0,2 to 0,3
Quantity per box	(1) 100 (2) 1000	(1) 100 (2) 1000	100	1000	1000

Caps with o-ring

NBR: Nitrile-butadiene rubber.

Caps with o-ring for Schrader Pacific tire Hardware Solutions and VDO pressure sensor



	R-1424-3	37900-63	(1) 37900-65 (2) 37900-58	(1) 42321-69	(1) T8029-100 (2) T8029-20	T8030-100
	High-temperature with washer	High-temperature with washer (nitrogen inflated)	High-temperature with washer	-	-	-
Body material	Polyamide	Polyamide	Polyamide	Polyamide	Polyamide	Polyamide
Color	black	green	red	black	gris	green
Seal	NBR	NBR	NBR	NBR	NBR	NBR
Tightness torque (N. m)	0,2 to 0,35	0,2 to 0,35	0,2 to 0,35	0,2 to 0,35	0,2 to 0,35	0,2 to 0,35
Quantity per box	100	100	(1) 100 (2) 5000	(1) 100 (2) 20	(1) 100 (2) 20	100

AUTOMOBILE AIR-CONDITIONING PRODUCTS R134A AND 1234YF



STANDARD SHORT CORES



	42996-68	43000-68	43001-68
Valve washer	CR	FPM	HNBR
Tightness torque (N. m)	0,4 to 0,8	0,4 to 0,8	0,4 to 0,8
Fluid	R134a	1234yf	R134a
Quantity per box	10	10	10

SPECIAL CORE

Threaded body, only for use on appropriate vehicles nitrile butadiene rubber styrene-butadiene rubber



	32361-68
Valve washer	HNBR
Tightness torque (N. m)	0,56 to 1,13
Fluid	R134a
Quantity per box	10

LARGE BORE CORES



	37478-68	42393-68	41734-68	32421-68	32422-68
Valve washer	CR	EPDM	FPM	HNBR	HNBR
Tightness torque (N. m)	0,7 to 2,2	0,7 to 2,2	0,8 to 2,2	1,7 to 3,4	1,13 to 2,26
Fluid	R134a	R134a 1234yf	1234yf	R134a 1234yf	R134a 1234yf
Quantity per box	10	10	10	10	10

- HNBR: hydrogenated nitrile butadiene
- CR: polychloroprene.
- FPM: fluorocarbon.
- EPDM: ethylene propylene diene rubber

CAPS



NBR SBR: nitrile-butadiene styrene-butadiene

	41143-20	41199-20	43380-20	43374-20
Use	High pressure	Low pressure	Low pressure	High pressure
Thread	M8 x 1	M8 x 1	M8 x 1	M8 x 1
Washer	NBR SBR	NBR SBR	NBR SBR	NBR SBR
Tightness torque (N. m)	0,6 to 1,15	0,6 to 1,15	0,6 to 1,15	0,6 to 1,15
Fluid	R134a	R134a	1234yf	1234yf
Quantity per box	20	20	20	20

BOXES



66158-67	
Use	For R134A
Composition du kit	10 cores 32361 10 cores 32421 10 cores 32422 10 cores 37478 10 cores 42393 10 cores 42996 20 caps 41143 20 caps 41199 1 valve core screwdriver 65290-67



	66818-67
Use	For 1234 yf
Composition du kit	<p>10 cores 32421</p> <p>10 cores 32422</p> <p>10 cores 43000</p> <p>10 cores 41734</p> <p>10 cores 42393</p> <p>20 caps 43380</p> <p>20 caps 43374</p> <p>1 valve core screwdriver 65290-67</p>



T66690 T66690-10	Tool for tightening valve stems with Torque pre-set to 0.40 N.m.	Quantity per box
		1 10

Chapter 3

PASSENGER VEHICLE WEIGHTS.

Schrader Pacific tire Hardware Solutions offers a complete range of weights made of STEEL and ZAMAK

UTILITY VEHICLE WEIGHTS.

A range of weights for balancing utility and 4x4 vehicle rims made of steel and aluminium with hooks or adhesives

BALANCING PRODUCTS



BALANCING PRODUCTS



- Car weights for steel and aluminium rims 26
- Adhesive motorcycle and car weights 27- 28
- Weight kits and van weights 29
- Tools for weights 29
- Balancing beads 30-33

BALANCE WEIGHTS



▶ WEIGHTS WITH BUILT-IN SPRINGS FOR STEEL RIMS

Zinc coated



Zinc coated	Weight mass (g)	Quantity per box
S-6483-44	5	100
S-6511-44	10	100
S-6512-44	15	100
S-6513-44	20	100
S-6514-44	25	100
S-6515-44	30	100
S-6516-44	35	50
S-6517-44	40	50
S-6518-44	45	50
S-6519-44	50	50

Raw Zinc



Raw Zinc	Weight mass (g)	Quantity per box
65900-67	5	100
65901-67	10	100
65902-67	15	100
65903-67	20	100
65904-67	25	100
65905-67	30	100
65906-67	35	50
65907-67	40	50
65908-67	45	50
65909-67	50	50

▶ WEIGHTS WITH BUILT-IN SPRINGS FOR ALUMINIUM RIMS

Zinc coated



Zinc coated	Weight mass (g)	Quantity per box
41796-44	5	100
41797-44	10	100
41798-44	15	100
41799-44	20	100
41800-44	25	100
41801-44	30	100
41802-44	35	50
41803-44	40	50
41804-44	45	50
41805-44	50	50

ADHESIVE WEIGHTS FOR ALLOY RIMS




Extra plates Zinc-coated steel

Extra plates Zinc-coated steel	No. of bars per box	Division	Dimensions (mm)
65684-67 (adh. Norton)	50	4 x 5 g + 4 x 10 g = 60 g	Th. 3,6 width 19 long 148
66886-67 (adh. std)	50		
66121-67	100		Th. 4 width 19 long 140



Extra plates Zinc-coated steel

Extra plates Zinc-coated steel	No. of bars per box	Division	Dimensions (mm)
369-100	100	4 x 2,5 g + 4 x 5 g = 30 g	Th. 2,8 width 19 long 119



MOTORCYCLE	No. of bars per box	Division	Dimensions (mm)
33622-39	50	4 x 5 g + 4 x 10 g = 60g	Th. 4.8 width 15 long 108.5
66122-67	100	7 x 5 g + 6 x 2,5 g = -50 g	Th. 7 width 11 long 105

BALANCE WEIGHTS

► VAN WEIGHTS



	Weight mass (g)	Quantity per box
41211-67	30	50
41212-67	40	50
41213-67	50	50
41214-67	60	50
41215-67	70	25
41216-67	80	25

Parts sold in boxes

► WEIGHT KITS



Kit contents	Weights for sheet steel rims	Weights for aluminium wheels
66058-67	40 x 10 g 40 x 15 g 40 x 20 g 40 x 25 g 40 x 30 g 20 x 35 g	40 x 10 g 40 x 15 g 40 x 20 g 40 x 25 g 40 x 30 g 20 x 35 g

TOOLS FOR WEIGHTS



	Designation	Quantity per box
65463-67	All-purpose balance weight pliers with soft head	1
65797-67	Adhesive weight removal tool	1
66119-67	Rubber wheel with 6mm adaptor stem for removing glue residue from rims (max 4000 rpm)	1

ADHESIVE WEIGHTS FOR ALUMINIUM RIMS



65744-67



66089-67



65745-67



66970-67



Cutting module 65817-97
Spare blades 65816-67

For alloy rims	Designation	Weight (kg)	Dimensions (mm)
65744-67	Wall dispenser for adhesive weights 65743-67 and 66089-67, cutting tool incorporated.	5,2	500 x 420 (sold empty)
65745-67	Wall dispenser for adhesive weights 65743-67 and 66089-67, cutting tool incorporated.	8,1	
66970-67	Roll of 1200 adhesive epoxy steel weights of 5g. Th. 3.5 width 17.	5	Th. 2,7 ø = 33,5
66089-67	Roll of 1200 adhesive zinc-coated steel weights of 5g. Th. 3.5 width 19.	6	Th. 2,5 ø = 30

BALANCING BEADS FOR COMMERCIAL AND 4X4 VEHICLES

▶ ELECTROSTATIC CLING BALANCING BEADS

- The beads automatically balance the complete wheel assembly whatever the wheel position, on both trucks and trailers thanks to the centrifugal force effect.
- The wheel assembly remains balanced even when the vehicle is stopped.
- tire is balanced during its life time.
- No machinery needed.
- The product is environmentally friendly.
- Increases fuel economy and tire life.



	Contents		No. of packs per box
65115-67	113 g	4 oz	96
65116-67	142 g	5 oz	76
65117-67	170 g	6 oz	64
65118-67	227 g	8 oz	52
65119-67	282 g	10 oz	40
65120-67	340 g	12 oz	36
65121-67	397 g	14 oz	32
65122-67	454 g	16 oz	28

Parts sold in bags



Download the Counteract application for precise calculation of the appropriate quantity



INSTRUCTIONS

- To achieve maximum results, refer to recommended quantities chart for each tire size. Open the outer package and throw the inner bag into the tire. This method permits use of an inflating gauge to seat the tire on the rim.
The pressure inside the tire will collapse the bag containing the beads.
 - The beads will automatically balance the complete wheel assembly.
- To remove the beads inside the tire before retreading, use the vacuum cleaner page 154.

Each pack of beads is sold with one core 43078 and one red cap 37900.



	Designation	Tightness torque (N.m)	Quantity per box
37900-65	Cap for identification of bead-balanced tires.	0.2 to 0.35	100
37900-58			5000



	Designation	Tightness torque (N.m)	Operating pressure (bar)	Quantity per box
43078-69	Core specially recommended for bead-balanced wheels.	0.23 à 0.56	0 to 14	100

BALANCING BEADS FOR MOTORCYCLE/SCOOTER/BICYCLE

▶ ELECTROSTATIC CLING BALANCING BEADS



For the balancing of high-speed motorcycles (sport and racing bikes), consult a professional or contact us.



	Contents of the display case
61183-67	15 motorcycle bead kits 28+ (5x28/28g+5x28/57g+5x28/85g)
61184-67	15 motorcycle bead kits 57+ (5x57/57g+5x57/85g+5x85/85g)
61185-67	15 motorcycle bead kits 57/57 (15x57/57g)

BALANCING BEADS FOR MOTORCYCLE/SCOOTER/BICYCLE




Operation:

- For a smooth and comfortable ride
- When the balancing beads are installed inside the tire, the specially treated microspheres are distributed in the tire by the centrifugal force created by rotation of the wheel.
- As the force of the point of imbalance increases and moves the suspension system in an up and down movement, the inertia causes the beads to disperse in the opposite direction and moves rapidly until wheel balance is achieved.


Advantages:

- Reduces vibration for a more comfortable ride
 - Extends the lifespan of the tires
 - Saves fuel
- Eliminates the need for balancing weights
- Balances your wheels for the lifespan of the tire
 - Compatible with TPMS


► USE OF BEADS




Tire width	Back	Front
80 - 120 mm		28g
80-120 mm (BMW Telelever only)		57g
130 mm		57g
130 - 240 mm	57g	
250mm - 360 mm	85g	
195 - 205 mm	85g	



All-terrain/with Gripster		
Tire width	Back	Front
80 - 120 mm		57g
130 - 203 mm	57g	



Tire width	
10"	28g
12" and more	57g



Tire width	
<10"	57g
<12"	85g
>12"	113g

Chapter 4

USING INFLATING GAUGES.

For best use of inflating gauges, we recommend that you:

- Check that the needle is positioned at zero \pm 0.1 bar before each use
- Make sure you regularly bleed the compressed air network
- Use filtered, non-lubricated air
- Connect the device to a hose reel
- Regularly check airtightness of the intake and outlet hoses
- Not overtighten the intake side coupler
- Never lock the inflating gauge handle while in use

"DIRECCTE" APPROVAL FOR GAUGE APPROVAL

N° 16.10.821.007.4 du 28 december 2016

Regional directorate for competition, consumption, labour and employment.



"DIRECCTE" approves the quality insurance system implemented by SCHRADER S.A.S for the manufacture of mechanical manometers for automobile vehicle tires covered by E.C.-approved certificate models and for the affixing of their E.C. initial verification marks.

INFLATION AND COMPRESSED AIR EQUIPMENT












- [Electronic inflating gauges with handles.....36 - 37](#)
[wear monitor/gauge - schrad'DIGITAL - MOTO.](#)
- [Electronic inflation terminals.....38 - 39](#)
- [Presentation of the Pressure Gauge range.....40 - 41](#)
- [Electronic inflator gauges with handle.....42](#)
[DIGITAIR - EURODIGIT.](#)
- [Mechanical inflator gauges with handle.....43 - 44](#)
[UNIVAIR - EURODAINU.](#)
- [Mechanical inflator gauges with buttons.....45](#)
[MASTAIR - MAESTRO.](#)
- [Assembly diagrams - Inflation connectors and fittings.....46 - 49](#)
- [Bead setters/pump rings.....49](#)
- [Automatic winders and hose reels, blow gun.....50 - 51](#)
- [Compressed air equipment.....52 - 53](#)
- [Compressed air connectors.....54 - 57](#)



► CHOOSING A PRESSURE GAUGE



			
	Digit'air	Eurodigit	Univ'air
Low pressure	■	■	
Auto calibration	■	■	
	■	■	
	■	■	
	■	■	
	■	■	
	■	■	■
	■	■	■
Actuation	Handle	Handle	Handle
Display	Digital	Digital	Needle
Max overpressure	15 bar	15 bar	13,75 bar










MADE IN PONTARLIER, FRANCE



French-made pressure gauges are manufactured each day in Pontarlier, thanks to you!

► CHOOSING A PRESSURE GAUGE



		
Eurodainu	Mast'air	Maestro
		
		
Handle	Buttons	Buttons
Needle	Needle	Needle
13,75 bar	15 bar	7,5 bar



ELECTRONIC INFLATING GAUGES WITH HANDLE

AIR OR NITROGEN USE

DIGIT'AIR®

EURODIGIT®



0,10 to 11 bar



(1)
DIGITAIR

(2)
EURODIGIT



- EC approval certificate model LNE - 6952 rev. 3 of 1 July 2008.
- Conform to the European directive 86/217/EC and to standard AFNOR EN 12645

- Design - Robustness:
 - Very high level of measuring accuracy and maintenance of accuracy in the event of impact on the device
 - Strength: high-quality thermoplastic components
 - Corrosion-resistant thanks to internal mechanism made of specific materials
 - Air filtration in the indicator mechanism via microporous stainless steel and nickel silver filter
 - Device able to withstand accidental overpressure of 15 bar.

- Technology:
 - Automatic reset of zero on each inflation to prevent measurement drift
 - Resolution of 0.01 bar
 - Operating temperature: -25°C to +60°C
 - Easy to read, thanks to numbers with a height of 12 mm, display of the last smallest digit
 - Visual inspection of proper operation of digits on each pressurisation
 - Automatic turn on of pressure gauge when pressurised (Connection to the valve)
 - Automatic turn off when pressure removed or at constant pressure for more than 10 seconds
 - Battery service life: 10 years after manufacture in temperate environment (the battery is not replaceable)



initialisation Video

	Graduation	Hose 7 x 13 mm		Air inlet side Torquer	Use
		L (m)	Hose P/N		
(1) 39900-00	0,10 to 11 bar	1,5	39064-00	F-G 1/4	
(1) 39901-00	1,4 to 160 psi *	1,5	39064-00	F-G 1/4	
(1) 39902-00	10 kPa to 1100 kPa *	1,5	39064-00	F-G 1/4	
(2) 39927-00	0,10 to 11 bar	1,5	39064-00	F-G 1/4	
(2) 39929-00	1,4 to 160 psi *	1,5	39064-00	F-G 1/4	

* Sold for export only and according to local regulations.

Parts sold separately

MECHANICAL INFLATING GAUGES WITH HANDLE

AIR OR NITROGEN USE

UNIV^{AIR}



(1)
UNIVAIR



0,7 to 11 bar



(2)
UNIVAIR



- Certificate of EC approval for LNE model No. 6952.
- DIRECCTE quality system certificate of approval No. 14.10.821.003.4.
- Declaration of verification delivered with product.

- Air inlet connector F G 1/4
- Watertight performance reinforced with a transparent dial.
- Rubber protector around the measuring system.
- Very high measuring accuracy with this level of accuracy maintained in the event of an impact on the device.
- Robustness: IXEF material in glass fibre-reinforced high technology plastic.
- Safety handle.
- Corrosion resistant internal mechanism.
- Air filtered in the indicator mechanism by stainless steel and nickel silver micro-porous filter.
- Device resistant to accidental high pressure of 13.75 bar in compliance with the standard.

	Graduation	Hose 7 x 13 mm		Air inlet side Torquer	Use
		L (m)	Hose P/N		
(1)	39700-00	0,7 to 11 bar	1,5	39064-00	F- G 1/4
(2)	39702-00	0,7 to 11 bar / 10 to 160 psi *	1,5	39064-00	F- G 1/4



Parts sold separately

* Sold for export only and according to local regulations.
The LNE and DIRECCTE certificates apply only to pressure gauges graduated in bar.

MECHANICAL INFLATING GAUGES WITH HANDLE

AIR OR NITROGEN USE

EURODAINU



0,7 to 11 bar




(1)
EURODAINU

(2)
EURODAINU

- Elastomer protector covering the measurement system.
- Very high level of measuring accuracy and maintenance of accuracy in the event of impact on the device.
- Strength: high-quality thermoplastic components
- Safety handle.
- Corrosion-resistant thanks to internal mechanism made of specific materials.
- Air filtration in the indicator mechanism via microporous stainless steel and nickel silver filter
- Device able to withstand accidental overpressure of 13.75 bar.

 • Certificate of EC approval for LNE model No. 6951.
DIRECCTE quality system certificate of approval No. 14.10.821.003.4.
• Declaration of verification delivered with product.

	Graduation	Hose 7 x 13 mm		Air inlet side Torquer	Use
		L (m)	Hose P/N		
(1) R-1822-Z	0,7 to 11 bar	1,5	39064-00	F-G 1/4	
(2) R-1821-Z	0,7 to 11 bar / 10 to 160 psi *	1,5	39064-00	F-G 1/4	

* Sold for export only and according to local regulations.
The LNE and DIRECCTE certificates apply only to pressure gauges graduated in bar.

MECHANICAL INFLATOR GAUGES WITH BUTTONS

Use AIR or AZOTE

MAST' AIR

MAESTRO



(1)
MASTAIR

0,7 to 12 bar

0,7 to 6 bar

(2)
MAESTRO

TECHNOLOGY - DESIGN

- Easy to operate with integrated + and – buttons.
- Simple handling: swivel connectors (air inlet and outlet).

ROBUSTNESS

- ABS shock-absorbing material with easy hanging: "ear".
- Waterproof protective glass.
- Elastomer protector covering the measurement system.
- MastAir is capable of withstanding an accidental overpressure of 15 bar and the Maestro 7.5 bar.




- LNE model certificate of EC approval No. 25820.
- DIRECCTE quality system certificate of approval No. 14.10.821.003.4.
- Declaration of verification delivered with product.

	Graduation	Hose 7 x 13 mm		Air inlet side Torquer	Use
		L (m)	Hose P/N		
(1) 39000-00	0,7 to 12 bar	1,5	39064-00	R-0987-2 (Drake)	
(1) 39002-00	0,7 to 12 bar	1,5	39064-00	G 1/4 (39066-67)	
(1) 39100-00	0,7 to 12 bar / 10 to 170 psi *	1,5	39064-00	R-0987-2 (Drake)	
(1) 39106-00	0,7 to 12 bar / 10 to 170 psi *	1,5	39064-00	G 1/4 (39066-67)	
(2) 39003-00	0,7 to 6 bar	1,5	39064-00	R-0987-2 (Drake)	
(2) 39004-00	0,7 to 6 bar	1,5	39064-00	G 1/4 (39066-67)	
(2) 39103-00	0,7 to 6 bar / 10 to 85 psi *	1,5	39064-00	R-0987-2 (Drake)	
(2) 39111-00	0,7 to 6 bar / 10 to 85 psi *	1,5	39064-00	G 1/4 (39066-67)	

* Sold for export only and according to local regulations.
The LNE and DIRECCTE certificates apply only to pressure gauges graduated in bar.

EXAMPLES OF PRESSURE GAUGE ASSEMBLY





39066-67	39080-67	65088-67	65089-67
Adaptor G 1/4 for Mastair and Maestro	Adaptor G 1/4 with filter for Mastair and Maestro	Teflon-coated threaded quick Torquer G 1/4	Junction connector for hose ø int. 6 - 7 mm conical threaded G 1/4





39766-67	R-0153-1
Intermediate-sized nipple for inflating gauges with a G 1/4 air inlet Torquer	Intermediate-sized nipple for inflating gauges with a Torquer R-0987-2 (Drake)



INFLATION ACCESSORIES




CONNECTORS FOR HOSES WITH INTERNAL Ø OF 7 MM





	R-0985-2	R-0985-1	R-0986-2
Description	Valve side inflation nipple for hose 7 x 13 mm (Spare washer R-0518-2)	Nipple R-0985-2 in skin-pack for display purposes (Spare washer R-0518-2)	House Torquer, outlet side for hose 7 x 13 mm
Quantity per box	10	1	10

► EAR CLAMPS



	(* R-0987-2)	32264-67	67244-68
Description	Rotating nipple inlet side for hose 7 x 13 mm	Quick inflating nipple clamp Torquer, valve side	For Hose Ø ext. 13 mm
Quantity per box	10	1	10

► OTHER CONNECTORS



	41291-68 41291-09	R-0517-2	(* R-3500-2)
Description	Inflation nipple valve side for 8 mm hose (Spare washer R-0518-2)	Valve side inflation nipple for hose 5 x 10 mm (Spare washer R-0518-2)	Rotating nipple for flexible hose extensions ø int. of 5 mm
Quantity per box	10 500	10	10



7X13 HOSE FOR INFLATOR GAUGES



39064-00

Description	For DIGITAIR, EURODIGIT, UNIVAIR, EURODAINU, MAESTRO & MASTAIR
Lenght (m)	1,5
Type	Woven braid, rotating nut, nipple R-0985-2
Quantity per box	1

► RIGID BEAD SEATERS/PUMP RINGS

- (1)
- (2)
- (3)
- (4)



	(1)	(2)	(3)	(4)
	60806-67	60807-67	60808-67	60814-67
Dimensions (")	13	14	15	16
Spare washer	65211-67	65212-67	60815-67	65213-67
Quantity per box	1	1	1	1

PRESSURE GAUGES

▶ PROGRAMMABLE ELECTRONIC GAUGES GRADUATED FROM 0.35 TO 7 BAR/5 TO 100 PSI/35 TO 700 KPA

For checking pressure

AIR OR NITROGEN USE



(1)

Default display in bars.

- Accuracy: $\pm 1\%$.
- 0.05 bar increments 0.05.
- Easy to read: wide screen.
- Blue backlit dial (1).
- White lighting.
- Durable rubber grip handle.
- Programming of desired pressure.
- Automatic reset to zero.
- Automatic turn-off.
- Storage pockets.
- 2 interchangeable batteries CR2032 Lithium 3V.
- Blister packed.



(2)

graduated from 0.35 to 6.85 bar/5 to 99 PSI/35 to 685 KPA

	Dial	Weight (g)	Precision	Use
(1) 66126-67	Rectangular	57	1 % $\pm 0,05$ bar	
(2) 66127-67	Round blue lighting	222	1 % $\pm 0,01$ bar	

▶ READ DEPTH GAUGE & ELECTRONIC PRESSURE GAUGE

2 functions on one tool



- Automatic turn-off.
- Backlit dial.
- 2 interchangeable batteries CR2032.
- Tread depth or pressure gauge selection function.

	Pressure gauge	Tread depth gauge	Use
66185-67	<ul style="list-style-type: none"> • 0.35 to 6.8 bar [5-99 psi or 35-680 Kpa or 0.4-7.00 kg/cm²]. • Accuracy: 1 % $\pm 0,05$ bar 	<ul style="list-style-type: none"> • Graduated from 0 to 15 mm [0 to 19/32"]. • Zone colour according to depth <1.6 mm = coloured zone red 1.6 to 3.2 mm = coloured zone yellow >3.2 mm = coloured zone green • Precision: 0.3 mm. • Resolution: 0.1 mm. 	

PRESSURE GAUGES

▶ ELECTRONIC PRESSURE GAUGES WITH DIGITAL DISPLAY

For checking pressure

AIR OR NITROGEN USE



Schrad'DIGITAL



(1)

MOTORCYCLE



(2)

	Graduation	Descriptive	Use
(1)	60226-67 0,35 to 10 bar	<ul style="list-style-type: none"> • Special for low pressure. • Accuracy: 1 % ±0,05 bar. • Can be use from -10 to 50°C. 	
(2)	65044-67 0,35 to 7 bar	<ul style="list-style-type: none"> • Durable rubber grip handle. • 3 interchangeable LR44 batteries (included). 	



PRESSURE GAUGES



AIR USE

► PRE-PROGRAMMABLE ELECTRONIC WALL TIRE INFLATORS

For inflating, deflating and adjusting pressure after programming the desired pressure



(1)



(2)



Terminals delivered with non-return valve and wall mounting.
Terminals delivered without hose and connectors: ordered separately

	Graduation	Description
(1) 66541-67	0,3 to 10 bar	LNE approved France
(2) 65786-67	0,3 to 12,5 bar	Sold with bar as default but can be reprogrammed for PSI or KPA. Sold for export only and according to local regulations in Europe.



CE Déclaration de conformité livrée avec le produit.

► TECHNICAL PRECISIONS

- Reading precision: 0.02 bar.
- Inside or outside installation (IP66).
- Operating temperature: 0 to 60°C.
- Aluminium cabinet
- Ergonomic design, easy to use.
- Large backlit LCD display.
- Information on Psi or KPa equivalent (65786-67).
- 240 V required electrical supply
- Automatic zero setting before each use.
- Dimensions: 269 x 285 x 106 mm.
- Max air intake pressure: 15 bar.
- Conical thread F-G 1/4 air inlet connection.
- Conical thread F-1/1" outlet.
- Attachment hook for hose.
- Weight: 5.4 kg.



► INFLATION ACCESSORIES

40058-67	Hose ø7x13 mm, L = 10 m for cars, woven braid with 1 clamp connector R-0985 valve side, quick Torquer + G 1/4 inflator side
40059-67	Hose ø7x13 mm, L = 20 m for trucks, woven braid with 1 clamp connector R-0985 valve Side, quick coupler + G 1/4 inflator for side

AUTOMATIC WINDERS AND HOSES



Intensive use

- Automatic winders with spiral leaf spring 180° and 180° directionable base.
- Epoxy-coated steel sheet cabinet
- Reel mounted on 2 sealed ball bearings.
- Stainless steel-brass rotating washer.
- Hose guide and end stop.
- Installation: wall fixture, height 2m

INTENSIVE
USE

	Max. dimensions (depth. x h x th.) (mm)	Hose length (m)	Hose	Weight (kg)
S-0335-1	410 x 360 x 230	10	open-drum woven braided hose int. Ø 7 x 13 mm sold with rotating nipple R-0987-2.	12
S-0336-1	435 x 460 x 240	20		18
S-0337-1	540 x 500 x 270	30		25



- Automatic winder with spiral leaf spring 180° and 180° directionable base.
- Epoxy-coated steel sheet cabinet
- Hose guide and end stop.
- Connecting kit provided.
- Installation: wall fixture, height 2.50 m.




	Max. dimensions (depth. x h x th.) (mm)	Hose length (m)	Hose	Weight (kg)
66667-67	370 x 337	15	Polyurethane / PVC hose int. Ø 8 x 12 mm sold with threaded nipple G 1/4	7
66668-67	Spare hose 15 m for winder 66667-67			
65082-67	Threaded quick coupler G1/4			

▶ HOSE COILS



	Hose length (m)	∅ (mm)	Braid type	Operating pressure (bar)
S-6570-1	10	7 x 13	Woven	15
S-6571-1	20			
S-6572-1	30			

▶ COILED HOSES



	Length (m)	Description
65100-67	4	Polyurethane hose 6.5 x 10 mm. Equipped with fixed-rotating male thread G 1/4. Working pressure: 9 bar.
65255-67	6	
65101-67	8	

▶ PROGRESSIVE BLOW GUN




	Description
65098-67	Progressive blow gun with tapped curved nozzle G 1/4 on metal insert Max. operating pressure 10 bar Max. flow: 380 litre/min at 6 bar
65099-67	Blowing assembly, coiled hose L = 4 m. Fitted with blow gun 65098-67

COMPRESSED-AIR EQUIPEMENT

► COMPRESSED-AIR EQUIPEMENT

Clean and Dry air



COMPLETE UNIT:
Filter + Regulator + Lubricator 1/2" (photo 1):
order P/N 66141-67 + 66142-67 + 65414-67
+ 66143-67 + 66144-67 x 2.

- Complete compact FRL system 1/2".
- Alloy body.
- Maxi pressure 17 bar.
- BSPP connection.
- Metal tanks.
- Operating temperature: -10 to +65.5 °C.
- Use special oil P/N 65775-67.



Coalescing Filter 1/2"
with inter-module plate (complementary item):
order P/N 66146-67 + 66147-67.

MODULAR UNIT:
Filter + Regulator 1/2":
order P/N 66145-67 + 65414-67 +
66143-67 + 66144-67.



COMPRESSED-AIR EQUIPEMENT



	66141-67	66146-67	66142-67	66145-67	66143-67
Type	5 µm particle filters	Coalescence filter absorbing 0.01 µm	Regulator	Filter/Regulator 5 µm filter element	Lubricator
Orifice (")	1/2	1/2	1/2	1/2	1/2
Description	Tank with sight gauge, manual bleed	Tank with sight gauge, manual bleed	8 bar pressure release valve with decompression. Plastic nut for panel mounting	Tank without sight gauge, manual bleed 8 bar pressure release valve with decompression. Sold with plastic nut for panel mounting	Tank with oil mist sight gauge, standard viewing dome
Max. flow (dm ³ /s)	38	11	67	64	47
Dimensions ht x width x depth. (mm)	188 x 60 x 60	209 x 60 x 60	136 x 60 x 60	245 x 60 x 60	182 x 60 x 60
Weight (g)	280	320	410	530	310
Additional information	-	Place a particle filter upstream	-	-	-



	66148-67	65414-67	66144-67	66147-67	66149-67	66554-67
Description	Manifold block 4 tapped ports: inlet/outlet 3/4" - top 1/4" - bottom 1/2" Max. flow: 64 dm ³ /s Dimensions: h 48 x width 66 x depth 73mm Weight: 340 g	Double graduation gauge 0-20 bar. 0-285 PSI Weight 53 g	Wall connection/ fixture bracket kit 1/2" with 2 O rings for hole ø 22.1 mm	1/2" connection kit with 2 O rings for hole ø 22.1 mm	Connection kit for 1/2" to 3/4" Must be ordered with 2 x 66147-67	Connection kit for 1/2" to 1/4" Must be ordered with 2 x 66147-67

COMPRESSED AIR CONNECTORS



	65082-67	66617-67	66738-67	65083-67	65084-67	61288-67
Description	Threaded quick coupler		Threaded quick Y-shaped double coupler	Threaded quick coupler	Grooved coupler	
Tapping (Gaz BSP)	G 1/4	G 1/2	G 1/2	G 1/4 Teflon coated	6 - 7	8
Ø air passage (mm)	6	6	6	6	6	6
Flow (L./min.) at 6 Bar	883	883	883	883	883	883
Maxi operating pressure (bar)	16	16	16	16	16	16
Quantity per box	1	1	1	1	1	1

- Automatic sleeve Torquers featuring a clamp attachment system: effortless connection and total tightness.
- Abrasion, shock, crushing and vibration resistant materials.
- Optimum flow adapted to all pneumatic tools thanks to contoured plug.
 - Operating temperature: -15 to +70° C.

MISCELLANEOUS CONNECTORS

According to assemblies, use adaptor 65591-67 M1/4"-M1/4" (see page 227).




	65491-67	65578-67	65579-67
Description	Quick connect filter nipple for all air-hydraulic devices (except impact wrenches, see page 104) conical threaded G 1/4	360° bi-directional nipple. Keeps the hose straight and strain-free Improves handling and use of pneumatic tools and inflating gauges. F inlet: G 1/4 M outlet: G 1/4 Flow: 0 to 45 m³/h under 7 bar	Pre-set line regulator Mounted upstream of the pneumatic tool, the regulator adjusts the pressure to avoid an air over-consumption and an overpressure on tools. (except impact wrenches, see page 104) F Inlet/Outlet F: G1/4 Max. inlet pressure: 18 bar, outlet pressure: 8 bar Max. flow: 700 l/min
Quantity per box	1	1	1

COMPRESSED AIR CONNECTORS




	65086-68	65087-68	65088-67 65088-68	65085-68	61290-67 61290-68	65270-67	65089-67 65089-68
Description	Quick tapped connector		Conical threaded quick connector	Quick junction connector		Double junction connector	Junction connector
Tapping (Gaz BSP)	G 1/4	Michelin pitch with flat seal	G 1/4 teflon-coated	6 - 7	8	6 - 7	6 - 7
Ø air passage (mm)	6	6	6	6	6	6	6
Flow (L./min.) at 6 Bar	883	883	883	883	883	883	883
Maxi operating pressure (bar)	16	16	16	16	16	15	15
Quantity per box	10	10	1 10	10	1 10	1	1 10


▶ EXAMPLE OF AIRLINE AND FITTINGS



EXAMPLE OF EXTENSION MOUNTING



EXAMPLE OF EXTENSION MOUNTING



Chapter 5

SYMBOLS FROM HAZARDOUS PRODUCT LABELLING.

They are given for information. The products being subject to change, we make their material safety data sheets available to you.

The use of protective goggles and gloves is recommended during repair operations.

Paying close attention to legislation and the “CMR” decree (on carcinogenic, mutagenic and reprotoxic substances), Schrader Pacific Tire Hardware Solutions offers a range of substitution products without chlorinated hydrocarbons and aromatic hydrocarbons and compliant with REACH regulations.

Our tire repair patches are compliant with repair standards ECE-R108 and R109.

PART STORAGE.

To adhere to expiry dates, store the parts, products and vulcanizing solutions:



- In a dry and clean area
- Away from light and heat
- Recommended temperature: between 15 and 30°C (except in case of specific product information) Store in closed containers.
- Complete instructions for use in boxes or on request.
- Follow the mounting and implementation instructions for repairs according to “best practices”, i.e. in accordance with reparability criteria and performing each operation according to a defined procedure, regardless of the repair process chosen.



TRAINING:

Schrader Pacific Tire Hardware Solutions provides training on repair products.

PATCHES AND REPAIR PRODUCTS FOR TIRES AND TUBES





• PRC: Tube repair parts.....	60 - 61
• PRP: Tire repair parts ("mushrooms" type).....	62 - 63
• PRF: Parts for cold tire repair	64
• SDO+: patches for the repair of bias tires.....	65
• SCHRAD+: patches for the repair of radial tires.....	66
• SRR: Retread patches for radial tire repair	67
• Vulcanizing solutions, brushes, talc, gum.....	68 - 71
• Repair inserts.....	72
• Insert tools.....	73
• PUCK* range: emergency repair	73
• SLIME* range: sealant, emergency repair	74

PRP TUBE REPAIR PARTS

► PRP 3 - PRP 4,5 - PRP 6 - PRP 8 - PRP 10

- (1) Up to the speed index J included for a maximum of 2 repairs
 - (2) Up to the speed index T included.
- Comply with local legislation in all cases. It may vary from one country to the next.



A: Tire tread B: Tire sidewall
NR: Not repairable zone

	Use	BIAS-PLY				RADIAL-PLY			
		A		B		A		B	
		PRP 3	PRP 6	PRP 3	PRP 6	PRP 3	PRP 4,5	PRP 6	PRP 3
(1)	Scooter 10" (Zone T)	X				X			
(1)	Motorbike & scooter (Zone T)	X	X (1)			X	X(1)	X(1)	
(2)	Passenger car	X	X	X	X	X	X	X	X(2)
(2)	Van & 4x4	X	X	X	X	X	X	X	X(2)

RAPID AND RELIABLE REPAIR:

- Specially designed for punctures made by nails, screws, bolts even in the tire sidewall.
 - The tire must be dismantled to assess its condition and suitability for repair.
- Repair from the inside of the tire. This is the only way of ensuring a quality reliable and safe repair. Structure of tire protected against moisture optimising the possibilities of retreading.
 - PRP range adapted for all types of tire according to the table below. Efficient permanent and immediately ready for further service.
- Quick and easy repair. Efficient, permanent and immediately ready for further service (Number of repairs allowed per tire is not limited except for motorcycles).


► BRUSHES FOR SOLUTIONS



60038-67	65076-67	67223-67	65864-67
Flat brush width 40 mm, L = 210 mm	Flat brush width 65 mm, L = 225 mm	Empty tin + top-brush for vulcanizing fluid	Rounded brush Ø 32 mm, L = 330 mm

PRP TUBE REPAIR PARTS

► BOX OF PARTS



- Parts also recommended for RUN-FLAT Tires, as per manufacturer recommendations.



	S-4953-8	42866-67 (1) 42903-67 (2)	S-4956-8 (1) 42392-67 (2)
	PRP 3	PRP 4,5	PRP 6
Ø pièces (mm)	3	4,5	6
Quantity per box	40	40 (1) 80 (2)	24 (1) 48 (2)
	3 years after date of manufacture		

► REPAIR KITS



Tube of vulcanizing solution for p79 kits
Stitcher roller R-5028-1
Spherical rasp S-4394-1



S-4252-8 Mini kit	S-4958-8 Kit
24 PRP Ø 6 mm Solution: 5 x 20 mL 1 year angular milling cutter Ø 6 mm	40 PRP Ø 3 mm 24 PRP Ø 6 mm Solution: 10 x 20 mL 1 year angular milling cutter Ø 3 mm 1 year angular milling cutter Ø 6 mm 1 spherical rasp (S-4394-1) 1 stitcher roller (R-5028-1)

PRC TUBE REPAIR PARTS




► BOX OF PARTS



- Once the repair is finished, sprinkle the part with talc to prevent the PRC from adhering to the inner tube (see talc on page 71).













PRF expiry date: 5 years after date of manufacture.

	Dimensions of parts (mm)	Quantity per box			
Rounded patches					
60500-67	Ø 25	100	•		
60501-67	Ø 30	100		•	•
60502-67	Ø 37	30		•	•
60503-67	Ø 45	30		•	•
60504-67	Ø 54	30			•
Oval patches					
60509-67	74 x 37	30		•	•



Choose the repair part according to the size of the injury on the tube.



► SOLUTIONS AND TOOLS

• Stir the solution before use.



R-5027-1	R-5028-1	60515-67	65941-67	60516-67	60719-67	60718-67 + 60717-67
Wire brush L. 188 x 1.17 mm	Stitcher roller	Tin of TOPAZE solution 250 mL	Set 250 mL TOPAZE 60515-67 + top-brush 60719-67	Tin of TOPAZE solution 720 mL	Top-brush for TOPAZE 250 mL	Top-brush for 720 mL



TOPAZE solution expiry date: 4 years after date of manufacture.

PRF COLD REPAIR FOR RADIAL AND BIAS TIRES

► BOX OF PARTS



• Use OPALE chemical vulcanizing solution.


	Dimensions of parts (mm)	Quantity per box
60700-67	Ø 35	100
60701-67	Ø 45	50
60702-67	Ø 60	50
60703-67	Ø 67	50
60704-67	Ø 35	500
60705-67	Ø 45	500
60706-67	Ø 60	500



PRF expiry date: 5 years after date of manufacture.

• Tread repairs only.
• Speed code restrictions: comply with local laws that can be different in each country

Tire use	Tire speed symbol	T = Ø (mm) max. TREAD prepared	PRF Ø 35mm	PRF 45x45mm	PRF Ø 50mm	PRF 60x60mm	Max number of repairs
	<J	3	X				2
		4.5		X	X		2
	J-V	6				X	1
		3	X				1
	<H	4.5		X	X		Unlimited
		6				X	Unlimited
		3	X				Unlimited
	H-ZR	4.5		X	X		1
		6				X	1
		3	X				1
	W-ZR	4.5		X	X		1
		6				X	1
		3	X				1
		<H	3	X			
4.5				X	X		3
6							3
8							3
10							3
V-Z		15					3
		3	X				1
		4.5		X	X		1
		6				X	1
		8					1





SDO+ PATCHES FOR BIAS TIRES



- For tread, shoulder and sidewall injuries: centre of injury = centre of patch.
- <=>The direction of the arrow printed on the patch indicates the radial bead to bead direction.



Shelf life of SDO+ patches: 5 years after the packing date.

	Description	Dimensions of parts (mm) W. x L.	Number of plies	Quantity per box		
60651-67	SDO+03	100x100	2	10	X	X
60652-67	SDO+04	120x120	2	10	X	X
60653-67	SDO+05	160x160	4	10	X	X
60655-67	SDO+06	240x240	6	10	X	X
60657-67	SDO+07	295x295	6	10	X	X
60659-67	SDO+08	345x345	6	5	X	X
60665-67	SDO+020	255x255	4	10	X	X
60666-67	SDO+021	370x370	4	5	X	X
60665-67	SDO+020	255x255	4	10	X	X
60666-67	SDO+021	370x370	4	5	X	X

- Cold: use the **OPALE** vulcanizing solution.
- Hot: use the **BLACK CEMENT** solution.
- SRR patch expiry date: 2 years after the date of manufacture.
 - Detailed instructions provided inside each box.
 - See REP marking page 157.



SCHRAD+. PATCHES FOR RADIAL TIRES



- For cold or hot vulcanization.
- For tread, shoulder and sidewall injuries: centre of injury = centre of patch.
- <=>The direction of the arrow printed on the patch indicates the radial bead to bead direction.



Shelf life of Schrad+ patches: 5 years after the packing date.

	Description	Dimensions of parts (mm) W. x L.	Number of plies	Quantity per box		
60600-67	SCHRAD+110	55x75	1	20	X	X
60601-67	SCHRAD+112	70x115	1	10	X	X
60602-67	SCHRAD+114	85x130	1	10	X	
60603-67	SCHRAD+115	90x75	1	20		
60604-67	SCHRAD+120	80x125	2	10		X
60605-67	SCHRAD+122	75x175	2	10		X
60606-67	SCHRAD+124	75x220	2	10		X
60607-67	SCHRAD+125	115x125	3	10		X

- Parts also recommended for RUNFLAT Tires (according to recommendations in table).
 - Use the OPALE vulcanizing solution.
 - Hot: use the BLACK CEMENT solution.
- SR patch expiry date: 5 years after the date of manufacture.
 - Detailed instructions provided inside each box.
 - See REP marking page 98.



S.R.R. RETREAD PATCHES FOR RADIAL TIRES



- Sidewall, shoulder and tread injuries:
centre of injury = centre of patch.
- <=>The direction of the arrow printed on the patch indicates the radial bead to bead direction.



Shelf life of SRR patches: 2 years after the packing date.

	Description	Dimensions of parts (mm) W. x L.	Quantity per box		
66330-67	SRR01	65	50	X	X
66331-67	SRR10	65x80	10		X
66332-67	SRR12	70x115	10		X
66333-67	SRR14	75x145	10	X	
66334-67	SRR20	75x125	10		X
66335-67	SRR22	75x165	10		X
66336-67	SRR24	75x215	10		X
66337-67	SRR26	75x250	10		X
66338-67	SRR33	100x125	10		X
66341-67	SRR40	100x200	10		X
66342-67	SRR40A	100x200	10		X

The suffix A in the description indicates that the product is Aramide reinforced for increased strength, flexibility and performance

- Cold: use the **66311-67** vulcanizing solution.
 - Hot: use the **66210-67** solution.
- SRR patch expiry date: 2 years after the date of manufacture.
- Detailed instructions provided inside each box.
 - See REP marking page 98.

COLD TIRE DAMAGE REPAIR



References			PRC	PRP	PRF
(1)	Topaze	Solutions	■		
(2)	Opale				■
(3)	Saphir			■	
(4)	Chemical Rasp	Rasp	■	■	■
(5)	Onyx	Finish/seal	■	■	■

SOLUTIONS



(1)	60515-67	65941-67	60516-67
	TOPAZE can of vulcanizing solution 250 mL	Set of 250 mL can TOPAZE vulcanizing solution 60515-67 + brush cap 60719-67	TOPAZE 720 mL can of vulcanizing solution
	4 years		



(2)	60710-67	65613-67	60712-67
	OPALE+ solution (18 to 150°C) (250 mL can), CFC-free	Set of OPALE+ solution 250 mL 60710-67 + brush 60719-67	OPALE+ solution (18 to 150°C) (720 mL can), CFC-free
	4 years		



(3)	S-4933-1 (*) S-4933-9 (**)	S-4948-1 (*) S-4948-0 (**)
	SAPHIR 20 mL vulcanizing solution tube	SAPHIR 20 mL vulcanizing solution tube SAPHIR 100 mL vulcanizing solution tube
	Packaging: 1 (*) Packaging: 50 (**)	Packaging: 1 (*) Packaging: 25 (**)
	2 years	



Insert	Patch Schrad+	Patch SRR	Patch SD0+	Patch with gum
■	■			■
■	■	■	■	■
	■	■	■	

CHEMICAL VULCANIZING SOLUTIONS



(4)	60518-67 (*) 60518-68 (**)	60519-67	60520-67
	Chemical vulcanizing solution 800 mL Packaging: 1	Chemical vulcanizing solution 5 L	Chemical vulcanizing solution spray 500 mL
	Packaging: 1 (*) Packaging: 10 (**)		
	5 years		2 years
	+25°C +15°C		

FINISHING PRODUCT




(5)	60730-67
	ONYX finishing product/ sealing of the repair perimeter 250 mL
	15 months
	+25°C +15°C

TOP-BRUSHES



60719-67	60718-67 + 60717-67
Top-brush for 250 mL OPALE, TOPAZE, ONYX	Top-brush for 720 mL


COLD REPAIR OF EXTERNAL DAMAGE WITH SELF-VULCANIZING RUBBER











References	PRC	PRP	PRF
(1)	Rubber A+B		

References	PRC	PRP	PRF
(2)	Self-vulcanizing bonding gum		

HOT DAMAGE REPAIR 100°C

References	PRC	PRP	PRF
(3)	Black Hot		
(4)	Hot bonding gum		
(5)	Tread gum roll 2.5 kg		





(1)	60731-67	(2)	60732-67	(3)	61392-67	61393-67
	Rubber A + B (2 boxes de 300 g)		Self-vulcanizing bonding gum		Hot vulcanizing solution BLACK HOT 2 (100 to 160°C), CFC-free	Hot vulcanizing solution BLACK HOT 2 (100 to 160°C) (3.5 kg jug), CFC-free
	1 year		2 years		1 year	
	2x300g		5Kg		800 mL	4,5 L
	-		Th.0,8 x l. 500 x L. 10000		-	
	   +25°C +15°C		 +30°C +15°C		   +25°C +15°C	

Insert	Patch Schrad+	Patch SRR	Patch SD0+	Sans Patch
	■	■	■	■

Insert	Patch Schrad+	Patch SRR	Patch SD0+	No Patch
	■	■	■	■

Insert	Patch Schrad+	Patch SRR	Patch SD0+	No Patch
	■	■	■	■
	■	■	■	■
	■	■	■	■



(4)	60733-67
	Hot binding rubber
	1 year
	Th. 1 x l. 500 x L. 8000

(5)	60734-67
	Hot sealing rubber
	1 year
	2,5Kg
	Th. 1,2 x l. 250 x L. 7200
	+25°C +15°C

65834-67
Talc (shaker)
640g
+25°C +15°C


EMERGENCY REPAIR FROM THE OUTSIDE



► INSERTS FOR RADIAL TIRES

- This type of repair is classified as an **EMERGENCY REPAIR ONLY** and after use the vehicles can be driven at max. 50 MPH for max. 50 miles.
- The tire should then be examined by a specialist as soon as possible to assess its structure and make a permanent repair.
 - Not for use in H, V or Z speed rated tires.
 - For injuries up to 6 mm maximum.



 Inserts are long-life products

	15-280
Quantity per box	60
Vehicle and tire type	Car radial tire
Length (mm)	100

► INSERT KIT

Use the **OPALE** or **JADE** cold solution.



	65410-67
Kit contents	1 "T" insertion tool 15-227 1 "T" reamer tool 15-225 30 inserts, L = 100 mm 1 can of "OPALE" vulcanizing solution 250 mL.



► **TOOLS**



15-224	15-225	15-227	15-231	15-230	15-232
Open Eye T-handle needle insert tool	Tire probe	Split-eye needle insert tool	Truck metal split-eye needle insert tool	Replacement needle for 15-231	Spiral grip cement needle tool

EMERGENCY REPAIR

► **AEROSOL TIRE INFLATORS**



- Used for emergency repair of a tire with or without tube after puncture in the tire tread. Do not use for tire sidewall repairs.
 - Repairs of punctures from the outside are only EMERGENCY REPAIRS.
- As soon as possible, have the tire dismounted by a professional for determination of the structural condition and definitive repair.
 - **Do not use the preventive product if there is a pressure sensor in the tire.**

Long life products



	A02299-67 (Per unit) A02299-12 (box of 12)	A07193-67 (Per unit) A07193-12 (box of 12)
Packaging	Aerosol 300 mL.	Aerosol 500 mL.
Manual	Remove the object that caused the puncture. Shake the aerosol vigorously. In cold weather, warm the aerosol for a few minutes by holding in hands. With the inflation valve in "12 o'clock" position, screw the connector onto the valve. Hold the aerosol in vertical position and press the button until completely empty (around 1 minute). Immediately drive at moderate speed for at least 5 km for the plugging product to expand.	

► LIQUID SEALANT FOR EMERGENCY REPAIR

www
@ Further information:
www.slime.com

Fibro-Seal™

- The SLIME puncture preventative seals punctures:
 - up to ø 3 mm maxi on tires with inner tubes
 - up to ø 6 mm maxi on tubeless tires.
- SLIME seals punctures on the TREAD area of the tire. The pressure of the escaping air forces the product into the opening and a plug is instantly formed.
- Liquid cleaned with water and non-toxic.
- Effective during the tire's entire lifetime.
- Used as a flat preventative, SLIME is effective up to 80 km/h.
- Used as an emergency repair after a puncture on the tread area of the tire, a speed of 130 km/h should not be exceeded and as soon as possible the wheel should be dismantled by a professional to assess its condition and make a definitive repair.
- Do not use for repairs on the tire's sidewall.
- Do not use the preventative if there is a pressure sensor in the tire.
- Can be used from -30 to +80°C

Sold packaged by 6.

Expiry date: 5 years after date of manufacture. Product lifetime in the tire: 2 years.



S10015	S10016	SDS50030IN	S10031
For tubeless MOTORCYCLE tires 237 mL	For tubeless tires or spare product for SMART REPAIR 237 mL	UNIVERSAL For tubeless tires or spare product for SMART REPAIR kit - 473 mL	UNIVERSAL and OFF ROAD For tubeless tires 946 mL

www
Calculation simulator
available at:
www.slime.com



www.slime.com

RANGE 

▶ PORTABLE KITS FOR EMERGENCY TIRE REPAIR AND INFLATION OF TUBELESS TIRES



Quick repair of a flat without removing wheel, no need to wait for assistance







www
@ further information:
www.slime.com

- SLIME prevents punctures of up to ø 6 mm maxi on tubeless tires.
- SLIME seals punctures on the TREAD area of the tire.
- Liquid cleaned with water and non-toxic.
- Effective during the tire's entire lifetime.
- Used as an emergency repair after a puncture on the tread area of the tire, a speed of 130 km/h should not be exceeded and as soon as possible the wheel should be dismantled by a professional to assess its condition
- The tire should be examined by a specialist as soon as possible to assess its structure and make a definitive repair. Do not use for repairs on the tire's sidewall.
- If the tire is equipped with a pressure sensor, Schrader Pacific Tire Hardware Solutions recommends it be immediately replaced
- Expiry date: 5 years after date of manufacture. Product lifetime in the tire: 2 years.
- Can be used from -30 to +80°C

Fibro-Seal™

 **Shelf life: 5 years, lifespan of product in tire: 2 years.**



CRK0305IN	S50129	S50024
		
<p>SMART REPAIR kit</p> <p>Contents:</p> <ul style="list-style-type: none"> - 1 can 473 mL of liquid sealant ref. SDS-500-IN - 1 compressor 12 V - 1 rigid storage case - Accessories <p>Dimensions: 22 x 8 x 17 cm Weight: 1.4 kg</p>	<p>SAFETY REPAIR Kit</p> <p>Inflate Air or Air+liquid sealant Deflate button pressure gauge</p> <p>Contents :</p> <ul style="list-style-type: none"> - 1 can 450 ml de liquide sealant ref. S10180 - 1 compressor 12 V - 1 storage case - Accessoires <p>Dimensions : 20 x 25,4 x 7,62 cm Weight : 2.2 kg</p>	<p>MOTO REPAIR kit</p> <p>Contents:</p> <ul style="list-style-type: none"> - 1 can 237 mL of liquid sealant ref. 10016 - 1 compressor 12 V - 1 rigid storage case - 1 accessories bag - 1 pencil type tire gauge <p>Dimensions: 17 x 8 x 17 cm Weight: 1 kg</p>
<p>Spare can for compressor Safety 473 mL Ref. SDS50030IN</p> 	<p>Spare can for compressor 450 ml Réf. S10180</p> 	<p>Spare can for compressor Safety 473 mL Ref. S10016</p> 

*Slim: trademark



Chapter 6

The use of eye protection, protective shoes and gloves, and protective ear defenders is recommended during repairs. Follow the recommendations of the instructions for use

A WIDE RANGE.

Schrader Pacific Tire Hardware Solutions offers a range of equipment for professionals to meet their customers' requirements and to train and provide turnkey solutions for repair specialists, industry, public works and mining..., depending on the tire to be repaired, up to 63" and the type of repair, puncture or injury:

- Injuries skiving tools
- Supports and spreaders
- Vulcanizers and special devices

To register, contact our sales team.



FORMATION:

Schrader Pacific Tire Hardware Solutions provides training on repair products.

REPAIR TOOLS AND VULCANIZING EQUIPMENT











REPAIR TOOLS AND VULCANIZING EQUIPMENT



• Assembly examples	78 to 85
• Pneumatic grinders, fittings and tool holders	86
• Tips and tool holders	87, 89
• Skiving tools and accessories	89 to 94
• Vacuum cleaners	95
• Small hand tools	96-97
• Tire markers	98-99
• VULCASCHRAD and its components	100-101



BRUSHES FOR RUBBER


Brushing, skiving and cleaning	
	
S-4792-1	S-4370-1 S-4979-1

Conical rasps		1/2 spherical rasps and Round rasps (buffing wheels)		Cutting of external rubber	
					
67640-67 (*) 67639-67 (*)	60373-67 60374-67	67620-67 S-4374-1 67621-67	60349-67 60350-67 60355-67 60356-67 60358-67 60359-67	60339-67 60340-67 60341-67	60882-67

External crater rasping and internal rasping Butyl	
	
67620-67 S-4374-1 67621-67	60339-67 60340-67 60341-67



() tool adaptable but not recommended for grinder*







EXAMPLES OF GRINDER USE



() tool adaptable but not recommended for grinder*

EXAMPLES OF GRINDER AND BRUSH USE

Brushing, skiving and cleaning	
	
S-4792-1	S-4370-1 S-4979-1

Crater rasping on tire tread		External crater rasping and internal rasping Butyl		Cutting of external gum	
					
67640-67 (*) 67639-67 (*)	60373-67 60374-67	67620-67 S-4374-1 67621-67	60349-67 60350-67 60355-67 60356-67 60358-67 60359-67	60339-67 60340-67 60341-67	60882-67

() tool adaptable but not recommended for grinder*

EXAMPLES OF GRINDER AND BRUSH USE



65310-67



65309-67



65307-67



61364-67



65796-67



66800-67





Swivel option

65578-67

() tool adaptable but not recommended for grinder*

EXAMPLES OF GRINDER AND BRUSH USE

Skiving on tire tread			
			
61128-67	61129-67	61130-67	
			
61143-67	61144-67	61145-67	
Finishing rollers			
			
S-4789-1 65851-67		60887-67 60888-67 60889-67	
External crater rasping and wall rasping Butyl			
			
67649-67			
Brushing, skiving and cleaning			
			
66124-67 66125-67	60884-67	60885-67	
Buffing rasp for tread and sidewall			
			
66689-67 66688-67	60382-67 60383-67	60376-67 60377-67	60379-67 60380-67

EXAMPLES OF GRINDER AND BRUSH USE



61132-67
61131-67



61146-67



65308-67



61364-67



65794-67



65795-67



66800-67






65796-67




Swivel option
65578-67

EXAMPLES OF GRINDER AND BRUSH USE

Cable cutter for sidewall for small damage	
	
61139-67	61137-67


Cable cutter for sidewall for significant damage or damage to tire tread

61140-67


61138-67

Buffing rasp for tire tread and sidewall

66962-67





AIR BUFFERS AND ADAPTATORS

WORK ON STEEL WIRES

WORKING ON RUBBER



	66801-67	66799-67	66800-67
RPM	22 000	800	4000
Power	253 watt (0.39hp)	335.56 watt (0.45 hp)	291 watt (0.39 hp)
Outlet shaft thread	3/8" with clamp of 6	3/8"	3/8"
Air consumption (L./min)	133	119	142
Noise level db(A)	103	95	101
Dimensions (mm)	L.175 x ø 50	L. 200 x l. 150 x ø 45	L. 248 x ø 50
Weight (kg)	0.6	1.34	1.06

Recommended
for TRP placement.

Chucks ordered separately

- Operating pressure: 6,5 bar. Filtered and lubricated air supply
- Follow the user instructions.

Connect
a quick Torquer
65088-67 onto the hose.



65796-67	65578-67	S 4788-1
Supply and exhaust kit for air buffer 66800-67, L = 74 cm	360° bi-directional nipple. Keeps the hose straight and strain-free Improves handling and use of pneumatic tools and inflating gauges. Inlet: G 1/4 female Outlet: G 1/4 male Flow: 0 to 45 m3/h under 7 bar	Spare collet 6 mm with keys for air buffer 66801-67

CHUCKS AND ADAPTATORS

▶ CHUCKS



65307-67	65131-67	65794-67	65795-67
For 66800-67 Quick chuck threaded 3/8" female x 24 UNF for air buffer 4000 r.p.m maximum	Chuck key 10 mm (replacement for 65794-67)	10 mm chuck with key for 66800-67	Automatic chuck 10 mm for 66800-67

▶ ADAPTATOR 10MM



	S 4310-1	60895-67	60893-67
Tapping	3/8"	M14	3/8"
Stem (mm)	6	8	8
Accessories		with 1 nut	with 1 collar nut

▶ FEMALE ADAPTATORS



	65446-67	65818-67	65308-67	65447-67	65448-67
Axle (mm)	3	4,5	6	8	10
Accessories	With Allen wrench	With Allen wrench	With Allen wrench	With Allen wrench	With Allen wrench
Intended use	For tools Ø 3 mm	For tools Ø 4,5 mm	For tools Ø 6 mm	For tools Ø 8 mm	For tools Ø 10 mm

▶ MALE ADAPTATORS



	65309-67	65310-67	65311-67	65312-67
Thread	3/8" x 24 UNF	3/8" x 24 UNF	M14	M14
Thread length (mm)	16	24	12	31
Accessories	With 1 nut	With 2 nuts	With 1 nut	With 1 nut

SHAFT MACHINES AND ACCESSORIES



- Powerful with a high torque motor and adapted speed to avoid burning rubber.
- Follow the user instructions.



	61364-67	61359-67	61360-67
Description	Electric shaft machine, Single speed 3000 rpm on 4-wheel trolley with flexible hose Ø 10	Flexible hose Ø10	Core of internal cord
Power	380 V, 750 W	-	-
Dimensions (cm)	100x77x77	200	± 200
Weight (kg)	50	2,75	0,90

TOOLS FOR SHAFT MACHINES AND PERSONAL PROTECTION EQUIPMENT



▶ 1/2 SPHERICAL RASPS

- Brushes are designed for brushing the rubber and cleaning skived areas or steel cables.
 - Speed: between 1400 and 4500 rpm.
- We advise you to wear protective goggles when using this equipment, along with protective gloves and our sleeves 61350-67



	60339-67	60340-67	60341-67
Grit	60	36	16
Ø (mm)	50	50	50
Width (mm)	25	25	25
Tapping	3/8" x 24 UNF	3/8" x 24 UNF	3/8" x 24 UNF

HQ
★★★★



	67620-67	S-4374-1	67621-67
Grit	TGG	GM	GF
Ø (mm)	50	50	50
Width (mm)	25	25	25
Tapping	3/8" x 24 UNF	3/8" x 24 UNF	3/8" x 24 UNF

Grit types:	Fine grit (GF) 60 or 170	Medium grit (GM) 36 or 230	Very large grit (TGG) 16 or 390

▶ TOOL HOLDER FOR BRUSHES



65307-67



61146-67

Hex (11 mm)

13 x 20

▶ TOOL HOLDER WITH BOTTLES



65794-67



65795-67



67251-67

S-4368-1

Ø stem (mm)	6	6
Ø Thread (mm)	10	10
Accessories	1 nut and 2 washers	1 nut and 2 washers

INTENSIVE USE

REFERENCES WITH "INTENSIVE USE" MARKING

Tungsten carbide rasps with even teeth. They are made up of a sheet metal holder electronically coated with a number of steel beads (depending on the grain size). These beads themselves are coated with a "conical head" made of tungsten carbide, using the same process. Even and smooth teeth provide more consistent shaping, better ventilation, heating the rubber less and releasing less smoke.

▶ **ROUND RASPS**



	60349-67	60350-67	60355-67	60356-67	60358-67	60359-67
Grit	36	16	36	16	36	16
Ø (mm)	50	50	50	50	50	50
Width (mm)	3,5	5	7	10	10	13
Tapping	3/8" x 24 UNF	3/8" x 24 UNF	3/8" x 24 UNF	3/8" x 24 UNF	3/8" x 24 UNF	3/8" x 24 UNF

▶ **AIRBOT**



	61128-67	61129-67	61130-67
Grit	14	14	14
Ø (mm)	50	50	50
Width (mm)	7	10	13
Hole hex. (mm)	11	11	11

▶ **CONICAL RASPS**

INTENSIVE USE



	67640-67	67639-67	60373-67	60374-67
Grit	TGG	GM	36	16
Ø (mm)	25	25	25	25
Width(mm)	102	102	102	102
Tapping	3/8" X 24 UNF	3/8" X 24 UNF	3/8" x 24 UNF	3/8" x 24 UNF



SKIVING TOOLS AND ACCESSORIES

- Rasps are recommended for rubber buffing and skiving.
 - Speed: between 1400 and 4500 rpm.
- We advise you to wear protective goggles when using this material.

▶ BALL AND CHIP RASPS

HQ
★★★★



	66689-67	66688-67	60382-67	60383-67
Grit	TGG	GM	36	16
Ø (mm)	20	20	20	20
Ø Stem (mm)	6	6	6	6

▶ CERAMIC EMULSION CYLINDRICAL RASP

HQ
★★★★



	S-4394-1
Ø (mm)	40
Ø Stem (mm)	6

- Cutter specially designed for buffing the tire before placing a PRP.
 - Recommended speed: between 1400 and 4500 r.p.m.

▶ PENCIL RASPS



	60376-67	60377-67	60379-67	60380-67
Grit	36	16	36	16
Ø (mm)	6	6	6	6
Width (mm)	65	65	102	102
Ø stem (mm)	6	6	6	6

▶ ROUND RASP

HQ
★★★★



	67649-67
Grit	GG
Ø (mm)	30
Width (mm)	6
Ø stem (mm)	6

▶ MINI-RASP KIT



	61142-67			
	(1)	(2)	(3)	(4)
Dimension (mm)	Ø15 x 3	Ø 10	Ø6 x 15	Ø3 x 25
Ø stem (mm)	3	3	3	3

► BRUSHES COMPLETE WITH STEM



	60884-67	60885-67
Ø (mm)	8	20
Th.(mm)	55	60
Ø stem (mm)	6	6

► PVC COATED BRUSHES WITH STEEL CORD



	66124-67	66125-67
Ø (mm)	8	8
Th.(mm)	63	76
Ø stem (mm)	6	8

Using these brushes reduces injuries.

► ANGULAR MILLING CUTTERS



	S-4946-1	65580-67	S-4947-1	65581-67	S-4954-1
Ø (mm)	3	4,5	6	8	10
Ø stem (mm)	3	6	6	8	10

► CUTTERS FOR METAL

- Speed: maxi 25,000 rpm.
- Use cutter 66801-67 with a Ø 6 mm stem (page 86).
- Use the stone for rubber tools P/N 60333-67.
- We advise you to wear protective goggles when using this equipment.



HQ
★★★★



	61137-67	61138-67	61139-67	61140-67
Grit	80	80	80	80
Type of cutter	Mushroom	Ball	Conical	Conical
Ø (mm)	40	20	25	65
Th. (mm)	10	-	8	20
Ø stem (mm)	6	6	6	6

FINISHING TOOLS

▶ ABRASIVES DISCS



	S-4789-1	65851-67
Ø stem (mm)	6	6
Width (mm)	15	30
Ø ext (mm)	60	60
Grit Ø	-	-
Description	-	-

▶ ROLLERS AND EMERY RINGS



	60887-67	60888-67	60889-67
Ø stem (mm)	6	6	6
Width (mm)	30	30	30
Ø ext (mm)	45	45	45
Grit Ø	60	60	40
Description	Complete with 5 rings	1 ring only	1 ring only

- Finishing tools allow to remove the vulcanized rubber excess.
 - Speed: between 1400 and 4500 rpm.
- We advise you to wear protective goggles when using this material.



SKIVING TOOLS AND ACCESSORIES

▶ CUTTING DISC

HQ



Sold per 1	66962-67
Ø disc (mm)	50
Ø hole (mm)	6

▶ GOUGE



	60882-67
Tapping	3/8" x 24 UNF
Ø gouge (mm)	32
Qty per box	Box of 3

- Speed: between 1400 and 4500 rpm.

TOOLS FOR SHAFT MACHINES

► BRUSHES FOR RUBBER



	S-4370-1	S-4979-1
Description	Set of 5 soft brushes	Set of 5 hard brushes
Ø (mm)	70	70
Th. (mm)	15/100e	35/100e
Ø hole (mm)	10	10

- Brushes are designed for brushing the rubber and cleaning buffed areas or steel cables.
- Speed: between 1400 and 4500 rpm.



65607-67

Grease cartridge for shaft machine inner core

Shaft machine inner core must be fully lubricated once a year.

► RUBBER BRUSHES



	61143-67	61144-67	61145-67
Description	Rubber brush	Rubber brush	Rubber brush
Ø (mm)	50	75	75
Th. (mm)	6	6	12
Ø hole (mm)	12,7	12,7	12,7

- Use :
- Tool order S-4368-1
 - Tool 67248-67



	S-4792-1
Description	Set of 2 plates + 1 washer
Ø (mm)	45
Th. (mm)	
Ø hole (mm)	10

Use: tool holders for brushes 65312-67 (Hex. 11 mm)

► STONE FOR RUBBER TOOLS



60333-67

Carbide stone with handle
170 x 30 x 20 mm for cleaning
of skiving tools for metal.

SPREADERS, REPAIR TABLE AND VACUUM KIT

► TIRE SPREADER



► MECHANICAL TIRE SPREADER



Order the filter-regulator combination unit separately:
Ref. 67374-67

	33705-67	67214-67
Description	Tire spreader for workbench	Highly mobile trolley L 55 x W 55 x H 115 cm.
Weight (kg)	3,5	35

► VACUUM CLEANERS



- Operating pressure: 6-8 bar.
- Supply with non-lubricated filtered air.










	65192-67	67215-67
Description	Pneumatic vacuum for dust and balancing beads	Vacuum cleaner 1100 W., 180 m ³ /h, tank 15 l. (bagless) with accessories
Weight (kg)	1,2	9,3
Connection	G 1/4	tapping G 1/4

SMALL HAND TOOLS





► KNIVES

	Description	Long blade (mm)	
	17-249	Curved knife	85
	17-248	Knife with straight blade 10 cm	100
	67227-67	Knife with ABS sleeve	160
	67228-67	Knife with ABS sleeve	120
	67229-67	Knife with ABS sleeve	280
	60338-67	Stone for rubber tools 230 mm	










► STITCHER ROLLERS AND PROBING AWL

	Description	Ø roller (mm)	Width (mm)	
	66383-67	Indicator of Ø for PRP and TRP L = 215 mm		
	R-5028-1	Stitcher roller	34	9
	60881-67	Toothed fine stitcher	25	2
	17-244	Toothed stitcher	38	2
	17-245	Toothed stitcher	38	6
	17-246	Toothed stitcher	50	6
	61182-67	Steel roller	40	46
	67225-67	Spur rowel	50	40
	67226-67	Box of 3000 points for stitcher 67225-67		

► CLAMP

		Description
	65219-67	Wire cutter for steel cables
	67221-67	Wire cutter for steel wires
	67220-67	Pliers
	65126-67	45° angled circlip pliers

► RUSHES, MALLET, RULE, SCREWDRIVER, SCISSORS, DEFACING TOOL

		Description	Long(mm)
	67218-67	Rubber mallet	320
	67222-67	Short shaft whisk broom	290
	67230-67	Rule	315
	65279-67	Steel convex brush	255
	65812-67	Grater	150
	66085-67	Stainless steel straight brush 0,35, 4 rows, body in beech	310
	60886-67	Scissors	Total: 200 Lames: 110
	67233-67	Tool for removing the tire registration number (delivered with its blade)	
	67234-67	Replacement blade	

TIRE MARKERS



If the tire marker is left on during breaks, it may overheat and get damaged.

60235-67

Description

Tire markers power 300 W.
Capacity 6 letters or numbers height 12 mm reaches its temperature after 20 min.

All letters and numbers available on request.



Extract from the «Tire repair Guide» printed by "Les professionnels du pneu"

"Tire repairs with patches and vulcanization in conformity with all repair process standards and control standards are marked with an indelible marking.

1) A mark inside clearly identifying the repairer will be affixed to the repair itself.

This marking will include the first six numbers of the repairer's RC (starting from the left) or name.

2) On the outside, a hot stamping will show "REP" on the fitting line vertical to the repair.

As of 1st January 2009, no more hot vulcanizing repairs on tire sidewalls can be made without the "REP" marking. Application for cars equipped with repaired tires according to professional practice code: as of 1 January 2012, all tires repaired on sidewall and according to professional practice code must be stamped with "REP" marking.

(1) tire marker (see above model)

(2) **65822-67** Aluminium plaque.



TIRE MARKERS

INTENSIVE
USE



INTENSIVE
USE



	60181-67	67469-67
Description	<p>"SUPER" MARKER Fitted with 135 x 64 mm rectangular head with groove. Ready for use after 20 minutes. The following items may be inserted:</p> <ul style="list-style-type: none"> - 15 separate figures or letters, height 10 mm - 10 separate figures or letters, height 20 mm - 1 personalised logo engraved on removable plate 	<p>"STANDARD" MARKER Fitted with 85 x 64 mm rectangular head with groove. Ready for use after 15 minutes. The following items may be inserted:</p> <ul style="list-style-type: none"> - 9 separate figures or letters, height 10 mm - 5 separate figures or letters, height 20 mm - 1 personalised logo engraved on removable plate
Power	400 W	200 W
Possible engraving area (mm)	135 x 64	85x64
Long (mm)	370	370
Weight (kg)	2	1,5

- These electrically heated marking appliances are used for marking tires by burning at a temperature of approx. 350°C.
 - The following items may be placed in the groove of "Standard", "Super" appliances:
 - Power 230 V single phase with earth

All letters and numbers available on request.

	Letter	Height (mm)
67471-1R	R	10
67471-1E	E	10
67471-1P	P	10

	Letter	Height (mm)
67472-2R	R	20
67472-2E	E	20
67472-2P	P	20

VULCANIZERS

"VULCASCHRAD"



Conform to EC Standard,
electromagnetic compatibility standard for
regulation: EN 61326.

SAFETY INFORMATION

- Vulcanization devices must always be operated under operator supervision.
- Disconnect the cabinet from the mains supply once vulcanization is complete.
- Never perform work in the cabinet without disconnecting the mains supply.
- These vulcanization equipment is equipped with a ground fault current circuit breaker for optimised operator safety.
 - Vulcanization equipment: Supply pressure max 2 bar.
 - Supply with filtered, non-lubricated air.

- Electronic setting to set the heating temperature according to the type of tire used, for optimum and simultaneous curing from the bead to the tire crown and regular pressure around the patch, especially at the shoulder.



	67295-67	67296-67
Applications		
Description	Vulcaschrad complete passenger car low profile	Vulcaschrad complete passenger car, passenger car low profile, light truck and 4 x 4
Tire series	30 to 80	30 to 85
Accessories included	<ul style="list-style-type: none"> • 2 moulds (Ref. 67297-67 and 65667-67) • 2 airbags (Ref. 67301-67 and 67319-67) 	<ul style="list-style-type: none"> • 3 moulds (Ref. 67297-67, 65667-67 and 67299-67) • 3 airbags (Ref. 67301-67, 67319-67 and 67303-67)
Power supply	230 V 2 P + T 16 A 30 mA	
Power (W)	800	
Tmer (Time)	0 - 12	
Weight (kg)	30 (67295-67)	38 (67296-67)
Heating mould temperature (max °C)	145	
Heating pad temperature (°C)	120	
Operating pressure (bar) dry air calibrated	2	
Maxi patch code	140	
Average curing time (mn)	60	
Cabinet dimensions (cm)	L. 20 x W. 20 x H. 30	
Device dimensions (cm)	L. 106 x W. 30 x H. 54	

COMPONENTS FOR "VULCASCHRAD"



▶ SPARE PAD



67382-67	
Description	External heating pad
Type	TCR
Dimensions (cm)	32 X 21

▶ SPARE MOULDS



65667-67		67297-67		67299-67	
Description	Sidewall mould	Sidewall mould	Sidewall mould	Sidewall mould	Sidewall mould
Applications	Low profile				
Tire series	30 to 65	65 to 80	65 to 80	75 to 85	75 to 85

▶ INTERMEDIARY PROTECTIONS



67382-67	
Description	Intermediary protection with fixtures

▶ SPARE AIRBAGS



67319-67		67301-67		67303-67	
Description	Sidewall airbag	Sidewall airbag	Sidewall airbag	Sidewall airbag	Sidewall airbag
Applications	Low profile				
Tire series	30 to 65	65 to 80	65 to 80	75 to 85	75 to 85

▶ DOUBLE SECTION PAD



67308-67	
Description	Double section pad



Chapter 7










THE LABELLING SYMBOLS FOR HIGH-RISK PRODUCTS ARE GIVEN

for information purposes only. The products are liable to change and their safety sheets are available at your disposal.

GARAGE EQUIPMENT, ASSEMBLY PRODUCTS, TOOLS AND PPE



TIRE MOUNTING PRODUCTS, WORKSHOP RANGE AND VEHICLE PROTECTION

	<ul style="list-style-type: none"> • Loosening 104 - 108 <ul style="list-style-type: none"> _____ Impact wrench, pneumatic grease _____ Impact socket
	<ul style="list-style-type: none"> • Lifting 108 - 109 <ul style="list-style-type: none"> _____ Hydraulic and portable jack _____ Jack stand
	<ul style="list-style-type: none"> • Products for mounting and dismounting of tires: 110-112 <ul style="list-style-type: none"> _____ Grease, cream, gel, lubricant, sealing product and brushes
	<ul style="list-style-type: none"> • Chalk and STYLMARK 111
	<ul style="list-style-type: none"> • Workshop services: lubricant, degreaser, soap 111-112
	<ul style="list-style-type: none"> • Vehicle protection 113
	<ul style="list-style-type: none"> • Hand tools 114 - 121 <ul style="list-style-type: none"> _____ Personal protective equipment _____ Control of tire wear _____ General tools _____ Tools for valves _____ For mounting and dismounting of tires _____ For handling

LOOSENING

- Maximum operating pressure: 6 bar, filtered and lubricated.
Lubricate and clean tools with the recommended products
- Pressure relief kit must be used to keep pressure at 6 bar (see below table).
 - To preserve impact wrenches, use the necessary filters.
- Wheel nut tightness must be checked after 25 to 40 km and again after another 100 km, then regularly.
 - Wear ear protection.
 - Follow the user instructions.

► IMPACT WRENCHES



	66669-67	65805-67	65807-67
Code	KP-1469A	KP-1434	KP-1450
Square (")	1/2	1/2	1/2
Handle	Revolver	Revolver	Revolver
Impact system	Single	Double	Double
Body and Handle	Metal	Metal	Composite
Air exhaust	Under Handle	Under Handle	Under Handle
Speed (rpm)	10000	8000	8000
Torque (N.m)	678	814	949
Weight (kg)	1,55	2,7	2,25
Lenght (mm)	120	184	178
Air inlet connector (")	G 1/4 F	G 1/4 F	G 1/4 F
Shaft	Short	Short	Short
Air consumption (l/min)	133	113	125
Acoustic pressure dB(A)	97	95	96
Noise level dB(A)	108	106	107
Acoustic pressure dB(C)	110	119	109
Vibration level (M/S ²)	10,3	8,8	10,2
Pressure relief kit: 6 bar limit (order separately)	66816-67		

• Wear ear protection.



► **PRESSURE RELIEF KIT LIMITING PRESSURE TO 6 BAR FOR IMPACT WRENCHES**



	66816-67	66817-67
Air inlet connector (")	G 1/4 F	G 3/8 F
For Hose Ø (mm)	7	12



61270-67	66091-67
KP-1488	KI-30
1/2	3/4
Revolver	Revolver
Double	Double
Composite	Metal
Under the Handle	Under the Handle
9500	5500
1356	1492
2,30	5,6
190	220
G 1/4 F	G 3/8 F
Short	Short
207	269
99,2	98,35
110,2	109,35
125	99
13,32	9,13
66816-67	66817-67

► **AIR INLET CONNECTORS**



65088-67	65845-67
Conical G 1/4 pre-Teflon-coated threaded quick connect fitting	Conical G 3/8 pre-Teflon-coated threaded quick connect fitting, air passage 11 mm

► **PNEUMATIC TOOL LUBRICANT**



65775-67
Special lubricant for pneumatic tools with lubricating agents and anticorrosion agents. 2-litre can
 FDS



Expiry date: 2 years after the date of manufacture.

IMPACT SOCKETS 1/2"

▶ IMPACT SOCKETS SHORT 1/2"



	Dim. on flat (mm)	Ø ext. (mm)	W. (mm)
65059-67	17	26	38
65060-67	19	30	38
65061-67	21	32	38
65781-67	30	42	46
65782-67	32	44	46
65855-67	33	46	46

▶ IMPACT SOCKETS LONG 1/2"



60268-67	13	20,2	82
60269-67	16	25	82
60270-67	17	25,9	82
60271-67	18	26,9	82
60272-67	19	29,9	82
60273-67	21	31,9	82
60274-67	22	31,9	82
60275-67	24	35,9	82
60276-67	27	39,9	82

▶ IMPACT SOCKETS LONG 1/2" EXTRA THIN



60277-67	17	24	82
60278-67	19	26	82
60279-67	21	28	82

▶ IMPACT SOCKETS LONG 1/2" PROTECTED




66704-67	15	21,4	85
65056-67	17	23,6	85
65057-67	19	25,9	85
65058-67	21	27,8	85
66576-67	22	29,4	85




Protected sockets for aluminium rims and extra-thin sockets are only designed for use with hand tools. Tightening must be performed with a torque wrench.

3/4" VAN AND TRUCK IMPACT SOCKETS

▶ IMPACT SOCKETS SHORT 3/4"

	Dim. on flat (mm)	Ø ext. (mm)	W. (mm)
 66587-67	23	35	52
66588-67	24	36	52

▶ IMPACT SOCKETS LONG 3/4"

	Dim. on flat (mm)	Ø ext. (mm)	W. (mm)
 66577-67	23	35	85
66578-67	24	36	85

▶ IMPACT SOCKETS KIT SHORT 1/2"



66701-67	Kit of 11 SHORT Car SHORT 1/2" (12, 13, 14, 15, 16, 17, 18,19, 21, 22, 24 mm)
-----------------	--

▶ IMPACT SOCKETS KIT LONG



66703-67	Kit of 5 protected truck sockets LONG 1/2" (15, 17, 19, 21, 22 mm)
-----------------	---



66702-67	Kit of 11 SHORT TRUCK LONG 1/2" (12,13, 14, 15, 16, 17, 18, 19,21, 22, 24 mm)
-----------------	--



66614-67

Extension VL 1/2",
length 125 mm

65225-67



Removal kit for car theft-proof nuts
(damaged nuts or special wrench).
Set of 2 reversible sockets: [21 x
24.5 x et 26 x 27.5] + extension



HANDLING, LIFTING

▶ ADJUSTABLE PROPS




Sold in pairs	450301	451600
Capacity (T)	3	6
Net weight (kg)	7	13,8
Min. height (mm)	305	395
Max. height (mm)	450	625
Base (mm)	209 x 185	293 x 263
Type	fixed	fixed

- 4-leg base: more stable, stronger and safer.
- Handle remains locked on loading (can serve as carrying handle).

▶ MOBILE AIR HYDRAULIC JACK



	410200	410600
Capacity (T)	2	6
Net weight (kg)	2,3	4,4
Min. height (mm)	158	197
Max. height (mm)	308	382
Total piston stroke (mm)	90	125
Extension screw (mm)	60	60
Base (mm)	96 x 93	116 x 116
Material	Steel	
Basic material	Caste iron	
Use	Horizontal or Vertical position	






HANDLING, LIFTING

► MOBILE AIR HYDRAULIC JACKS


(1) Ultra-light device, ideal for workshops and repair trucks, and for narrow environments. Designed for lifting low-floor vehicles.



(1)

	420250	420330	420500
Capacity (T)	2	3	5
Net weight (kg)	32	31	90
A: Min. height (mm)	75	120	150
B: Max. height (mm)	510	450	680
C: Width (mm)	343	344	366
D: Length (mm)	686	618	1505
E: Height (mm)	140	160	1345

► COLLARS



	65856-67	65857-67
h. (mm)	50	100

- High-resistance membrane with internal telescopic sliding.
 - Stop device and safety valve.
- Reliable and requires no maintenance.
- Silent, easy to use and light to transport.
- Supply with filtered, non-lubricated air.
 - Supply with filtered, lubricated air.

► PNEUMATIC PORTABLE JACKS



	65268-67 YAK 132	65354-67 YAK 203
Capacity (T)	2 t	2 t
Net weight (kg)	14 Kg	17 Kg
Power pressure (bar)	8 to 10 bar	8 to 10 bar
Air consumption	100 nL/min	100 nL/min
Max stroke	194 mm	285 mm
Min. height (mm)	132 mm	205 mm
Number of pistons	2	3
Piston stroke	97 - 97 mm	95 - 95 - 95 mm

TIRE MOUNTING AND REMOVAL PRODUCTS



▶ WHITE CREAM FOR TIRES

▶ BLACK CREAM FOR TIRES

▶ SPRAY LUBRICANT



UNIVERSAL	
65947-67	1 kg bucket (per unit)
65947-71	1 kg bucket (per 8)
65948-67	3 kg bucket
65949-67	5 kg bucket

UNIVERSAL BLACK	
66179-67	1 kg bucket (per unit)
66179-71	1 kg bucket (per 8)
66180-67	3 kg bucket
66181-67	5 kg bucket

SOCOLUB V 0690		
65023-67	400 mL	Per unit
	spray lasts for 100 montages	
65023-12		Per 12

Expiry date: 1 year after the packing date

Expiry date: 2 years after the packing date



Sealing product	
60813-67	1 L jug With brush cap

For tire paste and grease	
60804-67	Spare heads 66152-67

Chalks (box of 12)	
S-4305-1	White Ø 17 mm
S-4305-J	Yellow Ø 17 mm

Expiry date: 1 year after the packing date



Leak detector 500 mL	
65454-67	Concentrated product to be diluted with water

Empty spray for 65454-67	
65455-67	Empty spray for leak detector 500 mL

Expiry date: 5 years after the packing date

--	--



WORKSHOP SERVICE RANGE

▶ VEHICLE MAINTENANCE



High-gloss plastic aerosol		Quantity per box
A14878-67	High-gloss plastic silicone aerosol strawberry fragrance 500 mL	1
A14878-24		24
Use	For dashboard, trim, seats, etc. Cleans and gives shine to all plastic parts of the cabin with just one product. Its antistatic formula slows the accumulation of dust.	

Rim and hubcap cleaner		Quantity per box
A16286-67	Rim and hubcap cleaner in 500 mL spray	1
A16286-12		12
Use	Eliminates traces of grease and tar, dust, dirt and break pad residue. For use on aluminium and steel rims and plastic hubcaps.	



Expiry date: long life products

- The product freezes at 0°C.



Hand soap 5 L.	
66999-67	With wood microfibre. Ingredients gentle on skin.
Sold per unit	

Stylmark	
65763-67	Stylmark 3 mm yellow
65764-67	Stylmark 3 mm white
Suitable for all types of materials, all surface types 50 mL tubes.	



Expiry date: 2 years after the packing date



Expiry date: 3 years after the packing date



WORKSHOP SERVICE RANGE



► DRY DEGREASER AND LUBRICATING OIL

Expiry date: Long life products

Aluminium paste lubricant



	Packaging	Destination	Use
A19975-67 (Per unit)	500 mL. Spray	Static, antifriction lubricant for use at high temperatures and high pressures. Very useful for loosening aluminium rims attached to hubs.	(axle assemblies, bearings), in construction (pneumatic equipment, concrete pumps), in automobiles (o-rings of exhaust, housing, cylinder head).
A19975-12 (box of 12)			

Multi purpose lubricant



	Packaging	Destination	Use
A06332-67 (Per unit)	400 mL. Spray	Releases mechanical parts (screws, nuts, gears, chains, etc.). Lubricates and eliminates grinding. Prevents moisture, facilitates startup of engine and other ignition systems. Protects against rust. Dissolves grease, glue, tar. Facilitates machining, tapping, cutting, drilling, etc.	Silicone-free, inert, can be used on all materials. All-in-one diffuser operating in 2 ways: in the extender for wide diffusion or with the extender for diffusion in difficult-to-reach areas.
A06332-12 (box of 12)			

Brake cleaner



	Packaging	Destination	Use
A07500-67 (Per unit)	600 mL. Spray	Used to completely clean the brake system (discs, drums, trim, supports, springs, etc.). Also used as a degreaser for oils, dirty oils and greases, without leaving residue.	Automobiles and two-wheeled vehicles, brakes, chins, locks, mechanical parts, industry, the agricultural sector, etc.
A07500-12 (box of 12)			

VEHICLE PROTECTION



	Description	Dimensions	Parts/box	Information
	61271-67 Tire bag	Th. 50 µm, 70/30 x 100 cm Thickness compliant with new regulations (article 75-I of the Energy Transition for Green Growth law, modifying article L.541-10-5 of the environmental code).	100	Personalisation possible starting with 5,000 bags. Contact us.
 	61274-67 Plastic seat covers in dispenser		box 4 rolls of 100	Personalisation possible starting with 5,000 covers. Contact us.
	61286-67 Steering wheel protector	-	250	-
	61273-67 Black reusable PVC seat cover	85 x 135 cm	1	Note: not suitable for seats made of light coloured leather
	61275-67 Brown paper floor rug protector	-	100	Personalisation possible starting with 80 boxes of 500. Contact us.
	93898 Nitrile gloves, blue	Size L	100	-



PERSONAL PROTECTIVE EQUIPMENT

Recommended for buffing and skiving.

► Safety glasses



60306-67	60307-67	66084-67
High-protection glasses, adjustable arms with scratch-proofing, single screen with side protectors.	Safety overglasses with wide field of vision, lateral reflection-proof arms, ideal for corrective glasses.	Frame with monoblock panoramic screen in mist-proof and scratch-proof polycarbonate. Its front protection integrated with the screen ensures optimum coverage of the face without obstructing the field of vision. Rounded arms. 100% UV filtration. Come with nylon string. Standard: EN 166

Personal protective equipment for arms and hands



4.3.4.2

Dextérité : 5

Catégorie : II

61350-67	66082-67	66083-67
Cut-resistant sleeve ARACUT SLEEVE II, one size fits all.	Tear-proof repair gloves, size 9	Tear-proof repair gloves, size 10
Knit sleeve with 2-ply Kevlar®, thumb hole. Leather reinforcement on forearm	Dyneema®/ Lycra seamLess knit®/ grey printed polyester, induction polyurethane on palm and fingertips. Aerated back. Elastic sleeves. Colours: printed, induction grey. Length: 25 cm.	



► **Folding LED lamp**

	V2316
Description	Bendable 120° Rechargeable battery 3.6 V Battery life 3.5 – 4 hrs 5 LED = 300 lux at a distance of 60 cm 18 LED = 800 lux at a distance of 60 cm Weight approx. 200 g protection IP30






► **3M Versaflo**



61321-67	61349-67	61348-67	61351-67
Complete kit VERSAFLO TR315E+3M recommended to protect against dust for assisted breathing protection.	Replacement filter for 61321-67	Dust mask FFP2 S Light grey protective head covering T M/L	High-capacity battery from 10 to 12 hrs for Versaflo TR-300.
Includes filtration unit, anti-particulate filter, pre-filter, batter (10 to 12 hrs battery life), charger, hose and flowrate indicator			

A COMPLETE GARAGE TOOL RANGE



	Description
V3366	TORX® screwdriver set® 7 x  T10 · T15 · T20
V1409	T-handle Allen wrench set 8 x  2 · 2.5 · 3 · 4 · 5 · 6 · 8 · 10
V2820	Ratchet wrench set, long execution in soft pouch 5 x  8 · 10 · 13 · 17

▶ TREAD DEPTH GAUGE & ELECTRONIC PRESSURE GAUGE

2 functions on one tool



- Automatic turn-off
- Backlit dial
- 2 interchangeable batteries CR2032
- Tread depth or pressure gauge selection function

	Gauge	Tread depth gauge
66185-67	• 0.35 to 6.8 bar [5-99 psi or 35-680 Kpa or 0.4-7.00 kg/cm ²]. Measurement accuracy: 1 % ±0,05 bar	<ul style="list-style-type: none"> • Graduated from 0 to 15 mm [0 to 19/32"]. • Coloured zone depending on depth <1.6 mm = zone coloured red 1.6 to 3.2 mm = zone coloured yellow >3.2 mm = zone coloured green • Accuracy: 0.3 mm. Resolution: 0.1 mm



		Description	
V3734		Set of wrenches with 1/4" sockets in box	
	12 x		4 · 4.5 · 5 · 5.5 · 6 · 7 · 8 · 9 · 10 · 11 · 12 · 13 mm
	2 x		PH 1 · PH 2
	2 x		PZ 1 · PZ 2
	4 x		T 15 · T 20 · T 25 · T 30
	1 x		100 mm
	1 x		25 mm
	1 x		150 mm
V1571		Bubble level for steering wheel	

TIRES TREAD DEPTH GAUGE GRADUATED



Recommended for technical inspection

	Description	Graduation (mm)
S-4026-1	Tire tread depth gauge graduated	0 to 26
33640-67	Car tire tread depth gauge with case	0 to 11 (coloured area 0 to 1.6 mm according to EC standards 89.499)

TOOLS FOR VALVES



	Description
	S-4392-2 Standard car and truck valve cap and core screwdriver tool (without skirt)
	S-4049-2 Standard car and truck valve cap and core screwdriver tool (with skirt)
	65028-68 Car and truck valve cap and core screwdriver tool (without skirt)
	T66690 (*) T66690-10 (**) Standard valve core screwdriver tool with pre-set torque 0.40 N.m. (*) each (**) per 10
	S-4259-1 Core screwdriver and valve repair tool for repairing interior and exterior threads and removing broken cores
	R-0059-2 Core screwdriver tool also for performing minor repairs on the interior threads of car and truck valve mouths
	S-4282-1 Universal core screwdriver
	R-1255-1 Car and truck valve cap and core screwdriver tool
	T66885 Special lever for installation of TPMS valve
	S-4032-1 Lever for mounting of car rubber snap-in tubeless valves (metal handle)
	65027-67 Lever for mounting of car rubber snap-in tubeless valves (plastic handle)
	41-466 Valve removing tool ("DAUJY" type)

	Description	length (cm)	Weight (kg)
	S-4798-1 Flat tire dismounting lever for LV/ HGV for automatic machine	50	0,6
	33769-67 Flat tire removal lever, plastic liner for alloy rims	50	0,7
	65779-67 Car 4-way lug wrench 17-19-21 mm - 1/2" mâle	36	1,2
	65346-67 Hub cap removal tool	38	0,6
	65801-67 Plastic protector for edges of alloy rims		0,1
	R-1547-1 MOTO Specially for motorcycles 	38	0,5
	R-0425-1 FUSIL Lever for all tire types 	38	0,5

HANDLING



► Wheel tightening torque wrenches

- We recommend annual calibration.
- Follow the user instructions.



65240-67	
Description	Car (square 1/2"). Ratchet system. Audible click. Locking of torque adjustment jack. Guaranteed accuracy of $\pm 4\%$ of the reading on the scale (sold in plastic case)
Torque (N.m.)	40 to 200
Weight (kg)	1,2
Length (mm)	513



65778-67	
Description	Van and 4 x 4 (square 1/2") Accuracy $\pm 4\%$
Torque (N.m.)	40 pre-set
Weight (kg)	1,2
Length (mm)	435

- Secure handle locking
- Safety: tactile (short stroke triggering) and audible (click)
- Quick and safe adjustment of the desired value by turning the handle
 - User-friendly reversible ratchet
 - Integrated jack lever reducing accident and fault risks



HANDLING

► TROLLEYS AND WEDGES



61269-67	471105	471123
Wedge 385x155x180 mm yellow polypropylene	Tire cart, capacity 220 kg	Tire cart with wheels, load 160 kg



471147HD	4711SPP	471147HD + 4711SPP
Smart Car	Extension fo smartcar	Smart Car with extension

**ETRTO INDEX
INDEX OF REFERENCES
ALPHABETIC INDEX**

INDEX ETRTO

Reference		Page
ETRTO	Schrader Pacific Tire Hardware Solutions	
V1.10.1	R-1674-2	p15
V1.11.1	S-4043-2	p15
V2.01.1	S-4008-1	p14
V2.01.2	S-4010-1	p14
V2.03.1	R-1496-2	p12
V2.03.10	66501-80	p12
V2.03.10	S-4640-55	p14
V2.03.11	S-4640-66	p15
V2.03.12	35167-69	p16
V2.03.2	R-1496-3	p13
V2.03.2	R-0756-2	p12
V2.03.3	S-4636-55	p14
V2.03.3	R-0756-3	p13
V2.03.3	S-4156-2	p14
V2.03.4	S-4636-66	p15
V2.03.4	S-4638-55	p14
V2.03.4	R-1799-2	p12
V2.03.4	S-4156-3	p15
V2.03.5	66504-80	p16
V2.03.5	S-4638-66	p15
V2.03.5	R-1799-3	p13
V2.03.5	S-4156-55	p16
V2.03.6	S-4040-2	p12
V2.03.6	66507-80	p16
V2.03.6	S-4642-55	p14
V2.03.7	S-4040-3	p12
V2.03.7	S-4642-66	p15
V2.03.8	S-4040-55	p12
V2.03.8	R-1878-2	p12
V2.03.8	66513-80	p16
V2.03.9	S-4040-66	p12
V2.03.9	R-1878-3	p13
V2.04.1	R-1446-2	p16
V2.04.1	R-1510-2	p17
V2.05.1	S-4042-2	p16
V2.05.1	S-4042-G	p16
V3.23.1	43025-68	p13
V3.23.2	43025-69	p14

NUMERICAL INDEX

product	page	product	page	product	page
15-224	73	39702-00	39, 42	43374-20	21
15-225	73	39766-67	42, 43	43380-20	21
15-227	73	39900-00	38, 42	60038-67	60
15-230	73	39901-00	38, 42	60166-71	20
15-231	73	39902-00	38, 42	60181-67	99
15-232	73	39927-00	38, 42	60226-67	47
15-280	72	39929-00	38, 42	60235-67	98
17-244	96	40058-67	49	60268-67	106
17-245	96	40059-67	49	60269-67	106
17-246	96	41143-20	21	60270-67	106
17-248	96	41199-20	21	60271-67	106
17-249	96	41211-67	28	60272-67	106
41-466	118	41212-67	28	60273-67	106
369-100	27	41213-67	28	60274-67	106
4711SPP	121	41214-67	28	60275-67	106
30307-53	20	41215-67	28	60276-67	106
30307-54	20	41216-67	28	60277-67	106
30307-57	20	41291-09	44	60278-67	106
30307-58	20	41291-68	44	60279-67	106
30307-63	20	41558-68	14	60306-67	114
32264-67	44	41734-68	21	60307-67	114
32361-68	21	41796-44	26	60333-67	94
32421-68	21	41797-44	26	60338-67	96
32422-68	21	41798-44	26	60339-67	89
33622-39	27	41799-44	26	60340-67	89
33640-67	117	41800-44	26	60341-67	89
33705-67	95	41801-44	26	60349-67	90
33769-67	119	41802-44	26	60350-67	90
33792-69	20	41803-44	26	60355-67	90
35167-69	12	41804-44	26	60356-67	90
37478-68	21	41805-44	26	60358-67	90
37900-58	20, 31	42039-68	16	60359-67	90
37900-63	20	42039-69	16	60373-67	90
37900-65	20, 31	42321-69	20	60374-67	90
37992-69	20	42392-67	61	60376-67	91
37992-80	20	42393-68	21	60377-67	91
39000-00	41, 42	42396-67	15	60379-67	91
39002-00	41, 42	42563-68	17	60380-67	91
39003-00	41, 42	42564-68	17	60382-67	91
39004-00	41, 42	42866-67	61	60383-67	91
39064-00	38, 39, 40, 41, 45	42903-67	61	60500-67	62
39066-67	42, 43	42996-68	21	60501-67	62
39080-67	42, 43	43000-68	21	60502-67	62
39100-00	41, 42	43001-68	21	60503-67	62
39103-00	41, 42	43025-68	13	60504-67	62
39106-00	41, 42	43025-69	13	60509-67	62
39111-00	41, 42	43078-69	31	60515-67	63, 68
39700-00	39, 42	43249-68	17	60516-67	63, 68

NUMERICAL INDEX

product	page	product	page	product	page
60518-67	69	60886-67	97	65059-67	106
60518-68	69	60887-67	93	65060-67	106
60519-67	69	60888-67	93	65061-67	106
60520-67	69	60889-67	93	65076-67	60
60600-67	66	60893-67	87	65082-67	50, 54
60601-67	66	60895-67	87	65083-67	54
60602-67	66	61128-67	90	65084	49
60603-67	66	61129-67	90	65084-67	54
60604-67	66	61130-67	90	65085-68	55
60605-67	66	61137-67	92	65086-68	55
60606-67	66	61138-67	92	65087-68	55
60607-67	66	61139-67	92	65088	49
60651-67	65	61140-67	92	65088-67	42, 43, 55, 105
60652-67	65	61142-67	91	65088-68	55
60653-67	65	61143-67	94	65089-67	42, 43, 55
60655-67	65	61144-67	94	65089-68	55
60657-67	65	61145-67	94	65098-67	51
60659-67	65	61146-67	89	65099-67	51
60665-67	65	61182-67	96	65100-67	51
60666-67	65	61183-67	32	65101-67	51
60700-67	64	61184-67	32	65115-67	30
60701-67	64	61185-67	32	65116-67	30
60702-67	64	61269-67	121	65117-67	30
60703-67	64	61270-67	104	65118-67	30
60704-67	64	61271-67	113	65119-67	30
60705-67	64	61273-67	113	65120-67	30
60706-67	64	61274-67	113	65121-67	30
60710-67	68	61275-67	113	65122-67	30
60712-67	68	61286-67	113	65126-67	97
60718-67	63, 69	61288-67	54	65131-67	87
60719-67	63, 69	61290-67	55	65192-67	95
60720-67	70	61290-68	55	65211-67	45
60730-67	69	61321-67	115	65212-67	45
60731-67	70	61348-67	115	65213-67	45
60732-67	70	61349-67	115	65219-67	97
60733-67	71	61350-67	114	65225-67	107
60734-67	71	61351-67	115	65240-67	120
60804-67	110	61359-67	88	65252-68	16
60806-67	45	61360-67	88	65255-67	51
60807-67	45	61364-67	88	65268-67	109
60808-67	45	65023-12	110	65270-67	55
60813-67	110	65023-67	110	65279-67	97
60814-67	45	65027-67	118	65307-67	87
60815-67	45	65028-68	118	65308-67	87
60881-67	96	65044-67	47	65309-67	87
60882-67	93	65056-67	106	65310-67	87
60884-67	92	65057-67	106	65311-67	87
60885-67	92	65058-67	106	65312-67	87



NUMERICAL INDEX

product	page	product	page	product	page
65346-67	119	65822-67	98	66179-71	110
65354-67	109	65834-67	71	66180-67	110
65410-67	72	65845-67	105	66181-67	110
65414-67	53	65851-67	93	66185-67	46, 116
65446-67	87	65855-67	106	66210-67	67
65447-67	87	65856-67	109	66311-67	67
65448-67	87	65857-67	109	66330-67	67
65454-67	110	65864-67	60	66331-67	67
65463-67	28	65900-67	26	66332-67	67
65491-67	54	65901-67	26	66333-67	67
65578-67	54, 86	65902-67	26	66334-67	67
65579-67	54	65903-67	26	66335-67	67
65580-67	92	65904-67	26	66336-67	67
65581-67	92	65905-67	26	66337-67	67
65607-67	94	65906-67	26	66338-67	67
65613-67	68	65907-67	26	66341-67	67
65664-68	13	65908-67	26	66342-67	67
65667-67	101	65909-67	26	66383-67	96
65672-67	70	65941-67	63, 68	66501-80	12
65684-67	27	65947-67	110	66504-80	12
65744-67	29	65947-71	110	66505-68	12
65745-67	29	65948-67	110	66505-69	12
65752-68	13	65949-67	110	66505-80	12
65752-69	13	66058-67	28	66507-80	12
65753-68	13	66082-67	114	66508-69	12
65753-69	13	66083-67	114	66508-80	12
65754-68	13	66084-67	114	66513-80	12
65754-69	13	66085-67	97	66541-67	48
65763-67	111	66089-67	29	66554-67	53
65764-67	111	66091-67	104	66576-67	106
65765-68	17	66119-67	28	66577-67	107
65775-67	105	66121-67	27	66578-67	107
65778-67	120	66122-67	27	66587-67	107
65779-67	119	66124-67	92	66588-67	107
65781-67	106	66125-67	92	66614-67	107
65782-67	106	66126-67	46	66617-67	54
65786-67	48	66127-67	46	66667-67	50
65794-67	87	66141-67	53	66668-67	50
65795-67	87	66142-67	53	66669-67	104
65796-67	86	66143-67	53	66688-67	91
65797-67	28	66144-67	53	66689-67	91
65801-67	119	66145-67	53	66701-67	107
65805-67	104	66146-67	53	66702-67	107
65807-67	104	66147-67	53	66703-67	107
65812-67	97	66148-67	53	66704-67	106
65816-67	29	66149-67	53	66738-67	54
65817-97	29	66158-67	22	66799-67	86
65818-67	87	66179-67	110	66800-67	86

NUMERICAL INDEX

product	page	product	page	product	page
66801-67	86	420250	109	R-1510-2	17
66816-67	104, 105	420330	109	R-1533-2	15
66817-67	104, 105	420500	109	R-1547-1	119
66818-67	23	450301	108	R-1578-2	16
66886-67	27	451600	108	R-1674-2	15
66962-67	93	471105	121	R-1799-2	12
66970-67	29	471123	121	R-1799-3	12
66999-67	111	471147HD	121	R-1821-Z	40, 42
67214-67	95	A		R-1822-Z	40, 42
67215-67	95	A02299-12	73	R-1878-2	12
67218-67	97	A02299-67	73	R-1878-3	12
67220-67	97	A06332-12	112	R-1914-2	17
67221-67	97	A06332-67	112	R-2103-2	15
67222-67	97	A07193-12	73	R-3500-2	44
67223-67	60	A07193-67	73	R-5027-1	63
67225-67	96	A07500-12	112	R-5028-1	63, 96
67226-67	96	A07500-67	112	S	
67227-67	96	A07740-12	112	S-0335-1	50
67228-67	96	A07740-67	112	S-0336-1	50
67229-67	96	A14878-24	111	S-0337-1	50
67230-67	97	A14878-67	111	S-4000-3	20
67233-67	97	A16286-12	111	S-4000-5	20
67234-67	97	A16286-67	111	S-4003-2	14
67244-68	44	C		S-4008-1	14
67251-67	89	CRK0305IN	75	S-4010-1	14
67295-67	100	R		S-4026-1	117
67296-67	100	R-0059-2	118	S-4032-1	118
67297-67	101	R-0153-1	42, 43	S-4040-2	12
67299-67	101	R-0425-1	119	S-4040-3	12
67301-67	101	R-0517-2	44	S-4040-55	12
67303-67	101	R-0518-2	44	S-4040-66	12
67308-67	101	R-0638-3	20	S-4042-2	16
67319-67	101	R-0756-2	12	S-4042-G	16
67382-67	101	R-0756-3	12	S-4043-2	15
67469-67	99	R-0985	49	S-4049-2	118
67471-1E	99	R-0985-1	44	S-4156-2	14
67471-1P	99	R-0985-2	44	S-4156-3	14
67471-1R	99	R-0986-2	44	S-4156-55	14
67472-2E	99	R-0987-2	44, 50	S-4252-8	61
67472-2P	99	R-0990-2	14	S-4259-1	118
67472-2R	99	R-0990-3	14	S-4282-1	118
67620-67	89	R-1255-1	118	S-4305-1	110
67621-67	89	R-1424-3	20	S-4305-J	110
67639-67	90	R-1446-2	16	S 4310-1	87
67640-67	90	R-1496-2	12	S-4368-1	89
93898	113	R-1496-3	12	S-4370-1	94
410200	108			S-4374-1	89
410600	108				



NUMERICAL INDEX

product	page	product	page	product	page
S-4392-2	118	T			
S-4394-1	91	T8029-20	20		
S-4636-55	12	T8029-100	20		
S-4636-66	12	T8030-100	20		
S-4638-55	12	T66690	118		
S-4638-66	12	T66690-10	118		
S-4640-55	12	T66885	118		
S-4640-66	12	V			
S-4642-55	12	V1409	116		
S-4642-66	12	V1571	117		
S 4788-1	86	V2316	115		
S-4789-1	93	V2820	116		
S-4792-1	94	V3366	116		
S-4798-1	119	V3734	117		
S-4933-1	68				
S-4933-9	68				
S-4946-1	92				
S-4947-1	92				
S-4948-0	68				
S-4948-1	68				
S-4953-8	61				
S-4954-1	92				
S-4956-8	61				
S-4958-8	61				
S-4979-1	94				
S-6483-44	26				
S-6511-44	26				
S-6512-44	26				
S-6513-44	26				
S-6514-44	26				
S-6515-44	26				
S-6516-44	26				
S-6517-44	26				
S-6518-44	26				
S-6519-44	26				
S-6570-1	51				
S-6571-1	51				
S-6572-1	51				
S10015	74				
S10016	74				
S10031	74				
S50024	75				
S50053	75				
SDS50030IN	74				

ALPHABETICAL INDEX

product	page	product	page	product	page
1234yf	21	coils (hose)	51	hoses (inflation)	42 to 45
A		compressed air	36 to 57	I	
Accessories (TPMS)	108	compressed-air plugs	105	impact wrenches	104 to 105
adaptors	87 ; 89	compressed air connectors/couplers	54 to 57 ; 43 to 44	impact (socket, wrench)	107 ; 106 ; 117
adaptors (inflating gauges)	42 to 43	cores	20 to 21 ; 22 to 23	inflation	35 to 57
adjustable props	108	creams for tires	110	inflators	48 to 49
air-bags	100 to 101	cushion gum	70 to 71	inflating guns	51
air-conditioning	21	cutters	86 to 87 ; 78 to 85	inflation connectors/couplers	42 to 45
anti-puncture	74 to 75	D		inflator gauges	36 to 41
air buffers	86 to 87 ; 78 to 85	defacing tool	97	insertion (tools)	72 to 73
airtightness	110 ; 74 to 75 ; 68 to 69	degreaser	112	J	
awl	96	diagram (air buffers shaft machines)	78 to 85	junctions (inflation)	42 to 45 ; 54 to 57
B		DIGIT'AIR (manometer)	38 ; 36	K	
bags	100 to 101	discs	93 ; 84 to 85	kit (air-conditioning)	22 to 23
balancing (weights)	25 to 33	E		kit (braids)	72
bars (weights)	27	ear collars	44	kit (emergency repair)	72 to 75
beads	32 to 33 ; 95	emergency (repair)	72 to 75	kit (PRP)	61
bellows	109	EURODAINU	40 ; 37 ; 42	kit (vacuum)	95
blades	97	EURODIGIT	38 ; 36 ; 42	knives	96
blow gun	51	F		L	
BLACK HOT + (solution)	70	filler (gum)	70 to 71	lead (weights)	28
bottle jacks	108 to 109	filter	52 to 53 ; 56 to 57 ; 43	leak (finder)	110
braids	72 to 73	figures (for markets)	98 to 99	levers	118 to 119
brushes	60 ; 63 ; 69 ; 80 ; 82 ; 89 ; 92 ; 97 ; 94 ; 110	finish	93 ; 69 ; 82	lubricants	112
buffing solution	68 to 71	G		lubricator	52 to 53 ; 56 to 57
C		glasses	114 to 115	M, N	
camper (valves)	13	GLOBAL FRL SYSTEM	52 to 53 ; 56 to 57	MAESTRO (manometer)	41 ; 42 ; 35 to 37
caps	19 to 23	gloves	113 to 114	manometry	35 to 57
car extensions	17	glues	68 ; 63	mallet	97
car valves	10 to 17	gouges	93 ; 78 ; 80	markers	98 to 99
cement needle	72 to 73	grater	97	marking	98 to 99
chalks	110	grease (shaft machines)	94	MAST'AIR (manometer)	41 ; 37 ; 42
chrome-plated (valves)	12 to 13 ; 15 to 17	H		MICHELIN	36 to 37 ; 38 ; 40 ; 42 ; 46 ; 61 ; 68 ; 119
chucks	87 ; 89 ; 78 to 83	hammer	97	milling cutters	72 to 73
		handles (manometers)	35 to 41	moulds	100 to 101



ALPHABETICAL INDEX

product	page	product	page	product	page
mushrooms (PRP)	60 to 61	roller	82 ; 93 ; 96	tools (weights)	28
MOTORCYCLE (balancing beads)	32	rubbers	70 to 71	tools (small)	96 to 97 ; 118
MOTORCYCLE (lever)	119	rule	117	topaze	68 ; 63
MOTORCYCLE (pressure gauge)	47	S		torch	115
MOTO-REPAIR (Slime)	75	SAFETY-REPAIR (Slime)	74 to 75	torque wrenches	120
MOTORCYCLE (valve)	15 to 16	SAPHIR (solutions)	68	torque tools	120
MOTORCYCLE (weights)	27	scooter (valve)	137	TR 13-15	14
nipples/couplers (inflating)	42 to 45	sealant (repair)	110	TR 412-413-414 415-418-425	12 ; 14
needle	73	servo	95	TR 416-430	15 to 16
nipples/couplers (air buffers)	78 to 94	SCHRAD+	66	TR 600-801	13
O		SCHRAD'DIGITAL (pressure gauge)	46 to 47	training	8 to 9
OPALE (solutions)	68 ; 63	scissors	97	tread depth gauges	46 ; 116
P, Q		screens	100 to 101	tubeless	10 to 16
pad	101	screwdriver	116	tire supports	121
patches	62 to 67	SDO+	65	tire remover (levers)	119
penetrating oil	112	seals (rings)	45	tire spreaders	95
pliers	97	Serial number (tool)	97	tire paste	110
pliers (weights)	28	shaft machines	88 ; 81 ; 83	tire valves	118
pneumatic tool lubricant	105	Sleeve	114	U	
portable lamp	115	SLIME	74 to 75	UNIV'AIR (manometer)	39 ; 36 ; 42
PRC	62 to 63	SMART-REPAIR (Slime)	74 to 75	V, W, X, Y, Z	
press/machine (vulcanizing)	100	soap	111	vacuum cleaners	95
pressure gauges	46 to 47	SOCOLUB	110	valve core	20 to 21 ; 22 to 23
pressure relief kits	104 to 105	solutions	68 to 71 ; 63	valve core screwdriver	118 ; 22 to 23
preventive	74 to 75	spacer rings	101	versaflor	115
PRF	64	sprayer	110	vulcanizers	100 to 101
PRP	60 to 61	spreaders	95	VULCASCHRAD (vulcanizers)	100 to 101
programmable (inflator, pressure gauge)	48 to 49	STANDARD (marker)	98 to 99	vulcanizing solution	68 to 71
pump rings	45	stitchers	96	whisk broom	97
R		stone for rubber tools	94	weights	25 to 29
R134a	21	strings (repair)	72	weight unseater	28
rasps	89 to 94 ; 78 to 85	STYLMARK	111	winders	50 to 51
regulator	52 to 54	SRR	67	wrenches	
repair parts	60 to 75	SUPER (marker)	98 to 99	(lug, tightening)	119
rim protector	119	T		wrenches (impact)	106 to 107 ; 117
roll (weights)	29	talc	71	zamak (weights)	26
		technical assistance	8 to 9		
		theft-proof	107		
		tightness/tightening	118 to 120		
		tools (insertion)	72 to 73		

Direct lines for customer support:

Europe & Africa

Schrader s.a.s

48, rue de Salins - 25301 Pontarlier Cedex

Tel. +33 (0)3 81 38 56 27 - Fax direct +33 (0)3 81 38 56 81

E-mail : resale.info@schrader-pacific.fr

UK

Schrader Pacific Tire Hardware Solutions UK

Unit 1 Albion Buildings,

Kingfield Road, Coventry,

CV1 4NG - United Kingdom

Tel: +44 (0) 2476 550880 - Fax: +44 (0) 2476 220920

E-mail: reden@schrader-pacific.co.uk

Schrader s.a.s. - B.P. 29

48, rue de Salins - 25301 Pontarlier cedex

France

Tel. :+33 (0) 381 38 56 56 -

Fax : +33 (0) 381 46 41 42

E-Mail : general.info@schrader-pacific.fr



www.shop.schrader-pacific.fr